



New Location
 Drill Deeper
 Abandonment

Vol. XVII, P. 649

Violet Stanley
 ASD
 A/51

2.95 S
 2.84 C
 4 C (I-S)

Company WEST VIRGINIA GAS CORPORATION
 Address P.O. BOX 404 CHARLESTON, W.VA.
 Farm D.L. PITCHFORD ET AL
 Tract 75 Acres of 311[±] Lease No. 0V449-454-470
 Well (Farm) No. ONE Serial No. 062
 Elevation (Spirit Level) 836.20 (STADIA)
 Quadrangle KENNA - WC
 County PUTNAM District UNION
 Engineer W. S. GRAVELY
 Engineer's Registration No. _____
 File No. 3 Drawing No. WO 423
 Date DEC. 1, 1941 Scale 1" = 660

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. Put-159

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing

6-6-42

Deep Well

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Put 159

Company W.Va. Gas Corp.
Address Box 404, Charleston, W.Va.
Farm D.L.Pitchford et al acres 311
Location Rt. Fk. of Clendonin Creek
Well No One Serial #062 Elev. 836.2
District Union Putnam County
Surface D.L.Pitchford, Liberty, W.Va.
Mineral Same
Commenced Nov. 20, 1941
Completed March 24, 1942
Shot March 24, 1942 Depth 5031-5071
Flow 30/10ths W in 2" Depth 5031-5071
Volume 18 hrs. A.S. 231,000 C.F.
Fresh Water 83 3 blrs. pr. hr.
Salt Water 1600

Gas Well
CASING & TUBING
13 3/8 21'5 21'5
10 1/2 655'1 --
85/8 921'3
7" 2110'16
5 1/2 4985'3"

CASING CEMENTED:
5 1/2" -- 25 bags behind casing.

Slate Rock	0	25
Blue Slate	25	80
Sand	80	105
Red Rock	105	130
Sand	130	150
Blue Slate	150	230
Red Rock	230	285
Sand	285	320
Red Rock	320	355
Sand	355	380
Slate Shells	380	430
Sand	430	510
Slate	510	545
Red Rock	545	595
White Slate	595	725
Sand	725	747
Slate Shells	747	820
Sand	820	845
White Slate	845	920
Sand	920	965
Slate	965	1110
Sand	1110	1240
Slate	1240	1260
Sand	1260	1340
Slate	1340	1525
Salt Sand	1525	1830
Lime	1830	1992
Broken Sand	2080	2110
Black Lime	2110	2165
Slate	2165	2240
Slate & Shells	2240	2470
Black Shale	2470	2485
Berea Sand	2485	2500
Slate & Shells	2500	3950
Brown Shale	3950	4275
White Slate	4275	4675
Brown Shale	4675	4936
Corniferous Lime	4936	5031
Oriskany Sand	5031	5070
Lime	5070	5071
TOTAL DEPTH		5071

Show gas 2485

Gas 5034-5039 13/10 W 2"
Shot 3-24-41 from 5031 to 5071
with 300# 80% Gelatin
Test 18 hrs. A.S. 30/10 W 2"