

WR-38  
Rev (5-08)  
DATE: 10/02/2015

API # 47-079-00585-P

STATE OF WEST VIRGINIA  
DIVISION OF ENVIRONMENTAL PROTECTION  
OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPlicate, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm Name: John R. & Dorothy Manning Operator Well No. : J. R. Manning #1

LOCATION: Elevation 575 ft. Quadrangle: Saint Albans, West Virginia  
District: Poca District County: Putnam, West Virginia  
Latitude: 13,100 Feet South of 38 Deg. 45 Min. 00 Sec.  
Longitude: 11,300 Feet West of 81 Deg. 45 Min. 00 Sec.

Well Type OIL GAS XX

Company: Teavee Oil and Gas Inc.  
112 Brooks Street  
Charleston West Virginia 25301

Coal Operator NONE

Agent: Duane Bowers  
Permit Issued Date: 07/17/2015

AFFIDAVIT

STATE OF WEST VIRGINIA  
County of Putnam ss:

Richard Moore and Grover Butler being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the named well operator, and participated in the work of plugging and filling the above well, and Jamie Stevens Oil and Gas Inspector representing the Director, say that said work was commenced on the 14th day of September 2015 and that the well was plugged and filled in the following manner:

| Note: There is no 3-1/2", 4-1/2", found in this well  |      |      |  |   |
|---|------|------|--|---|
| TYPE  | FROM | TO   | PIPE REMOVED                             | LEFT  |
| GEL   | 4486 | 4386 | Perf's 4486 feet 6 holes                 | Could not pump through holes or pull tubing |
| GEL   | 4386 | 4171 | Cut 2-3/8 inch tubing @ 4196 feet        | 346 feet of 2-3/8 in.                       |
| CEMENT  | 4171 | 4000 | 15 sacks with latex paint added          |   |
| GEL   | 4000 | 3350 |  |   |
| CEMENT  | 3350 | 3250 | 15 sacks w/ latex paint Brown Shale      |   |
| GEL   | 3250 | 2100 |  |   |
| CEMENT  | 2100 | 2000 | Cement across Berea Sand                 |   |
| GEL   | 2000 | 1695 |  |   |
| CEMENT  | 1695 | 1595 | Cement across 5-1/2 casing shoe          |   |
| GEL   | 1595 | 1470 | Cut 5-1/2 casing @ 1435 feet             | 237 feet 5-1/2 inch casing                  |
| CEMENT  | 1470 | 1370 | Cement across 7 inch casing shoe         |   |
| GEL   | 1370 | 1070 | Cut 7 inch casing @ 1040 feet            | 367 feet 7 inch casing                      |
| CEMENT  | 1070 | 970  |  |   |
| GEL   | 970  | 600  |  |   |
| CEMENT  | 600  | 500  | Upper salt water 550 feet                |   |
| GEL   | 500  | 250  | Cement across 8-5/8 casing shoe          |   |
| CEMENT  | 250  | 0    | Cut 8-5/8 casing @ 180 feet              | 65 feet 8-5/8 inch casing                   |
|   |      |      | Pulled 45 feet of 10-3/4 inch casing *** | 110 feet 10-3/4 inch casing                 |
|   |      |      | Pulled 18 feet 13-3/8 inch casing        | Casing shoe on end of 13-3/8 inch casing    |
| *** 10-3/4 inch casing previously parted, found end of pipe had been belled out to sit down over collar. When 10-3/4 was pulled, old rags and cement was found around the bell section of pipe. |      |      |  |   |

DESCRIPTION OF MONUMENT: 7 " set 36" above ground API # and Date Plugged, welded on the side of pipe. And that the work of plugging and filling said well was completed on the 1 st. day of October 2015.

And further deponents saith not.

Richard Moore  
Grover Butler

01/22/2016

Sworn and subscribed before me this 19th day of October, 2015

My commission expires: 04/20/2018 Duane K. Bowers Notary Public

Oil and Gas Inspector: Jamie Stevens 1/12/2016

