

WR-38  
Rev (5-01)  
DATE: 11/03/2010

API # 47-079-01158-P

STATE OF WEST VIRGINIA  
DIVISION OF ENVIRONMENTAL PROTECTION  
SECTION OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPlicate, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm Name: W. A. McMillian

Operator Well No. : P-13

LOCATION: Elevation 670.92 ft. Quadrangle: Scott Depot, West Virginia  
District: Scott District County: Putnam, West Virginia  
Latitude: 2270 Feet South of 38 Deg. 27 Min. 30 Sec.  
Longitude: 4010 Feet West of 81 Deg. 52 Min. 30 Sec.

Well Type OIL \_\_\_\_\_ GAS XX

Company: Teavee Oil and Gas Inc.  
112 Brooks Street  
Charleston West Virginia 25301

Coal Operator NONE  
RECEIVED  
Office of Oil and Gas

Agent: Duane Bowers  
Permit Issued Date: 06/30/2010

AFFIDAVIT

FEB 17 2015

STATE OF WEST VIRGINIA  
County of Putnam

ss:

WV Department of  
Environmental Protection

Bradley P. Setliff and Christopher D. James being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the named well operator, and participated in the work of plugging and filling the above well, and Jamie Stevens Oil and Gas Inspector representing the Director, say that said work was commenced on the 28th day of September, 2010 and that the well was plugged and filled in the following manner:

Note: 5-1/2 inch casing rotten at top of well , dug 8 ft. deep, still rotten. Contacted inspector about perforations from 1475 feet to surface, permission granted, 9/27/10 Inspector on site				
Note: There is no 3-1/2", 4-1/2", 7" or 8-5/8" found in well				
TYPE	FROM	TO	PIPE REMOVED	LEFT
CEMENT	2100	2000	Berea Sand plug	342 feet of 2-3/8 in.
GEL	2000	1769	Cut 2-3/8 inch tubing @ 1769 feet	
CEMENT	1769	1600	Cement across top of Big Lime	
GEL	1600	1465	10 perfs 1475-1365 feet	
CEMENT	1465	1365	Cement across bottom of Salt Sand	
GEL	1365	1050	10 perfs 1050-950 feet	
CEMENT	1050	950	Cement across top of Salt Sand	
GEL	950	700	10 perfs 700-600 feet	
CEMENT	700	600	upper most salt water	
GEL	600	350	10 perfs 350-250 feet	
CEMENT	350	250	cement across lowest freshwater	
GEL	250	100	10 perfs 100 - 75 feet	1723 feet 5-1/2 casing
CEMENT	100	0	surface plug	Conductor of unknown length

DESCRIPTION OF MONUMENT: 7 " set 30" above ground API # and Date Plugged, welded on the side of pipe. And that the work of plugging and filling said well was completed on the 1<sup>st</sup> day of October 2010.

And further deponents saith not.

Bradley Setliff  
Christopher D. James

Sworn and subscribed before me this 4<sup>th</sup> day of October, 2010

02/20/2015

My commission expires: 01/20/18

Duane K. Bowers Notary Public

Oil and Gas Inspector: Jamie Stevens

Jamie Stevens

