



LATITUDE=

37' 50"

81 17 30

81 15

LONGITUDE



Found in 1916 Co. Rept
135 on Map II

7.5 OGIS topo location

7.5' loc	_____	15' loc	<u>2.645</u>
	_____	(calc.)	<u>3.88W</u>

Company Marsh Exploration
 Farm Creek Mankin
Creek Mankin

Eccles SE

Quad Eccles 7.5

County Blaine

District Trap Hill

WELL LOCATION MAP

File No. 081-0928

record of this latter well from Capt. Allen, except that depth of the well was about 1600 feet, and the material passed through was "Red rock and thin shells".

Another well was drilled on Dingess Branch of Mt. Fork, 2 miles north of Surveyor, the record of which is as follows:

Crock Mankin No. 1 Well Record (135).

Trap Hill District, on Dingess Branch, 2 miles north of Surveyor, authority, Marsh Fork Coal & Gas Co.; completed, October 11, 1916.

	Thickness.	Total.
	Feet.	Feet.
Soil	8	8
Sandstone, gray	35	43
Slate	5	48
Coal	1	49
Sandstone, gray	10	59
Sandstone, pebbly	154	213
Slate and shale	150	363
Sandstone, gray	23	386
Slate	25	411
Sandstone, white	124	535
Slate	7	542
Coal	4	546
Sandstone and slate	20	566
Coal	3	569
Sandstone and slate	12	581
Coal	2	583
Sandstone, brown	22	605
Sandstone, black	5	610
Slate	53	663
Sandstone, grayish, with streaks of black	24	687
Sandstone, white	67	754
Sandstone, black	20	774
Sandstone	14	788
Slate	7	795
Coal	5	800
Sandstone, gray	90	890
Slate	10	900
Coal	7	907
Sandstone, dark	19	926
Sandstone, gray	35	961
Sandstone, dark	12	973
Sandstone, gray, with light streaks	9	982
Sandstone with light streaks, base of Pottsville	25	1007
Shale, red	64	1071
Sandstone, gray	25	1096
Red shale	48	1144
Slate	70	1214
Sand	5	1219
Shale, black	70	1289

081
928

	Thickness.	Total.
	Feet.	Feet.
Sand and lime	8	1419
White sand	150	1427
Red rock	30	1577
Sand and lime	30	1607
Slate and shells	33	1637
Sand, shells and slate	50	1670
Slate and shells	116	1720
Pink rock and shells	50	1835
Red rock and shells	20	1885
Slate	30	1905
Pink rock and shale	30	1935
Sand shell and shale	45	1980
Slate and shells	20	2000
Pink rock	15	2015
Sand, shale and slate	40	2055
Pink lime and shale	19	2074
Shale, black	50	2124
Lime	11	2136
Slate	20	2155
Lime	15	2170
Shale	15	2185
Unrecorded to bottom	1315	3500

No oil or gas was found in any of the sands of this well.

OIL AND GAS PROSPECTING IN MERCER COUNTY.

Several years ago a well was drilled in the city of Princeton and Mr. Wirt French, the postmaster of that city, reports that the boring was sunk to a depth of about 1,700 feet, where the tools were lost in the hole and it was abandoned.

The following is a partial record of a well now being drilled in Rock District, Mercer County, being the second well drilled in the County:

Griffith No. 1 Well Record.

Rock District, Mercer County; 1 1/4 miles east of Spanishburg, on Rich Creek; commenced, December, 1915; still drilling, May, 1916; authority, Rich Creek Oil & Gas Company; elevation, 2090' B.

	Thickness.	Total.
	Feet.	Feet.
Clay	16	16
Lime, hard	35	51
Coal ?	2	53
Sand	52	105
Slate	35	140
Lime, dark, hard	12	152
Slate	42	194
Lime (hole full of water at 220')	41	235