



Well to be abandoned

Company	Godfrey L. Cabot, Inc.
Address	Grantsville, W. Va.
Farm	J. B. McQuain
Tract	One Acres 56+ Lease No. 3-7
Well(Farm) No	One Serial No. 517
Elevation (Spirit Level)	1090'
Quadrangle	Otter
County	Roane District Geary
Engineer	Logan McDonald
Engineer's Registration No.	610
File No.	Drawing No.
Date	1/15/37 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 Department of Mines
 , OIL AND GAS DIVISION
 Charleston

WELL LOCATION MAP
 File No. 1200-1516

+ Denotes location of well on U
 Topographic Maps, scale 1 to 62
 latitude and longitude lines be
 represented by border lines as

- Denotes one inch spaces on bo
 line of original tracing.

J. B. McQUAIN NO. 1 (517) WELL.

151A

Geary District, Roane County, W. Va.
 By Godfrey L. Cabot, Inc., Charleston, W. Va.
 Drilling commenced March 29, 1928; completed April 14, 1928
 (original hole, depth 1298').

8½" casing, 708'.

Well deepened; drilling commenced Sept. 23, 1936; completed,
 Oct. 15, 1936. Drilled from Salt Sand through Maxton;
 obtained no production--hole plugged and abandoned.
 Well abandoned and plugged Dec. 5, 1936.

	Top.	Bottom.
Soil	0	5
Red rock	5	350
Slate and shell	350	410
Sand	410	580
Slate	580	600
Sand	600	697
Slate	697	700
Sand	700	725
Break	725	730
Sand	730	815
Slate	815	850
Sand	850	875
Coal	875	878
Slate and shell	878	970
Sand	970	1000
Shale	1000	1050
Lime	1050	1075
Slate	1075	1140
Sand	1140	1189
Slate and shell	1189	1283
2nd Salt Sand (gas, 1286', 8/10 w. in 2"; gas, 1292-98', 82/10 w. in 2"; 24 hr. R. P. 385 lbs.)	1283	1298
WELL DEEPENED:		
Sand	1298	1305
Slate and shells	1305	1320
Lime, white	1320	1330
Slate, brown	1330	1338
Lime, white	1338	1350
Slate	1350	1355
Lime, gray	1355	1380
Slate, gray	1380	1384
Sand, white (small show gas, 1398' (hole full water, 1425'))	1384	1473
Lime, white	1473	1497
Slate	1497	1502
Lime, gray	1502	1520
Sand, white	1520	1530
Lime, gray	1530	1560
Sand, white	1560	1570
Slate, brown	1570	1580
Lime, gray	1580	1590
Slate, brown	1590	1592
Sand, white	1592	1630

(OVER)

J. B. McQUAIN NO. 1 (517) WELL (Continued).

	Top.	Bottom.
Slate, brown	1630	- 1638
Lime, gray	1638	- 1642
Slate, brown	1642	- 1649
Sand, white	1649	- 1697
Slate, brown	1697	- 1701
Little lime, black	1701	- 1702
Total depth		1702

GODFREY L. CABOT, INC.
WELL RECORD

J. B. McQuain #1, Serial #517
Geary District, Roane County

Size	Casing & Tubing Used in Drilling	Left in Well
8-1/4"	708'	708'

Drilling commenced - March 29, 1928
" completed - April 14, 1928 (orig. hole)

Soil	0	5
Bed Rock	5	350
Slate & Shell	350	410
Sand	410	580
Slate	580	600
Sand	600	697
Slate	697	700
Sand	700	725
Break	725	730
Sand	730	815
Slate	815	850
Sand	850	875
Coal	875	878
Slate & Shell	878	970
Sand	970	1000
Shale	1000	1050
Lime	1050	1075
Slate	1075	1140
Sand	1140	1159
Slate & Shell	1159	1283
2nd Salt	1283	1298

ROA-151-A

Gas 1286
Gas 1292-98

T 401
8/10 W. -2" 119 mcf
82/10 W. -2" 382 mcf
24 hr. R. P. 885#

Well Deepened

Drilling commenced - Sept. 23, 1936
" completed - Oct. 15, 1936

Sand		1298	1305
Slate & Shells		1305	1520
Lime	White	1320	1330
Slate	Brown	1330	1338
Lime	White	1338	1350
Slate		1350	1355
Lime	Grey	1355	1380
Slate	"	1380	1384
Sand	White	1384	1473
Lime	"	1473	1497
Slate		1497	1502
Lime	Grey	1502	1520
Sand	White	1520	1580
Lime	Grey	1580	1560
Sand	White	1560	1570
Slate	Brown	1570	1580
Lime	Grey	1580	1590
Slate	Brown	1590	1582
Sand	White	1592	1630
Slate	Brown	1630	1638
Lime	Grey	1638	1642
Slate	Brown	1642	1649
Sand	White	1649	1697
Slate	Brown	1697	1701
Little Lime	Black	1701	1702

Gas 1398
Water 1425

Small show
Hole full
Caves badly

(Drilled from Salt Sand through Maxton)
(obtained no production - hole plugged)
(and abandoned)

Total Depth

1702

Well abandoned and plugged 12/5/36

1298
404 New Fly.