

New Location.   
 Drill Deeper.   
 Abandonment.

NOV 20 1945

Company SUPERIOR PIPE & SUPPLY CO.  
 Address GRAND RAPIDS, MICHIGAN  
 Farm J.B. WHITED  
 Tract \_\_\_\_\_ Acres 100 Lease No. 15819  
 Well (Farm) No. 4568&10 Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) AS SHOWN  
 Quadrangle RIPLEY  
 County ROANE District CURTIS  
 Engineer J.A. Cunningham  
 Engineer's Registration No. 659  
 File No. 68-87 Drawing No. \_\_\_\_\_  
 Date Oct. 23, 1944 Scale 1" = 400'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON  
 ROA-424-A #10; ROA-425-A #5  
**WELL LOCATION MAP**  
 FILE NO. ROA-413-A-#4  
ROA-414-A-#6  
ROA-416-A-#8  
 + Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

Record of Well No. 714 on J. J. KELLED #5 Farm 100 Acres  
 HUNDARD Field CURTIS District HOANE County N. VA. State  
 Rig Commenced 19 Completed 19  
 Drilling Commenced Dec. 2 1918 Completed Dec. 15th 1918  
 Cost per Foot Contractor WILFRED BRGS. Address  
 Drillers' Names

740

BOILER		ENGINE				RIG	
No.	Name of Maker	H. P.	No.	Name of Maker	New	Old	Name of Builder

CONDUCTOR AND CASING USED IN DRILLING							
Conductor	12 inch	10 inch	8 1/2 inch	6 1/2 inch	4 1/2 inch	3 1/2 inch	2 inch

CONDUCTOR AND CASING LEFT IN WELL							
Conductor	12 inch	10 inch	8 1/2 inch	6 1/2 inch	4 1/2 inch	3 1/2 inch	2 inch

GAS WELL							
When Shot	Size of Torpedo	1st Day's Production	Tubing	Rods	Tanks	Size of Packer	Depth Set


FORMATION			REMARKS				
Top	Bottom	Thickness					

Pittsburgh 347 437 8" casing hanging on clamps - 20 ft. from bottom  
 Darkard 338 339

OIL FROM 339 to 346 Showed up for 40 barrels - Makes about 10 barrels water - all good rig.

Well shot March 10th, 1919 - Doubled production; original production 8 barrel before shooting.

BJA-425-A



NOV - 6 1918

Examined above information and measurements and found to be correct by Contractor \_\_\_\_\_ Superintendent of Co. \_\_\_\_\_  
 NOTE - The above blank must be filled out carefully by the contractor, with a complete and accurate record of the Well, and accompany when presented for payment of the bill for drilling.  
 All formations and known sands must be given by their proper name, with actual live measurements, and under the head of "Remarks" must be recorded in what sand and at what depth Oil, Gas or Water was found, the quantity of same, the quality of the sand, and thickness of pay.  
 Make no memoranda of boiler and engine if owned by contractor.

J. B. WHITED NO. 5 (V-1237) WELL. (714).

Curtis District, Roane County, W. Va.

By Union Gasoline & Oil Corporation.

On 100 acres.

Drilling commenced Dec. 2, 1918; completed Dec. 15, 1918.

Contractor: Nuhfer Bros.

Conductor, 16"; 10" 35# casing, 620'; 8 1/2" 24#, 826'. 8" casing hanging on clamps - 20 ft. from bottom.

Elevation.....' L.

Abandoned under permit Rit-.....-A?

Oil from 839 to 846' - showed up for 40 barrels - makes about 10 barrels water - all wood rig.

Well shot March 19, 1919; doubled production; original production, 5 barrels before shooting.

Record to Dept. of Mines not dated or stamped. OIL WELL.

Record to RCT from Mrs. Griffith Nov. 6, 1945. Old File No. 340.

	Top.	Bottom.
Pittsburgh Sand	347	437
Dunkard Sand (oil, 839-846')	832	839
Total depth		846