

70058

Harper District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced March 16, 1910, and completed March 16, 1910.

Drilling commenced April 6, 1910, and completed May 13, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers, Ed. Runniger and Sam Ferrill.

Oil in Salt Salt, 1292'; April 22, bailed 3 bbls.; Apr. 23, bailed 4 bbls.; Apr. 25, bailed 4 bbls.; Apr. 26, bailed 3/4 bbl.

Examined and approved by E. H. Lange, Foreman.

Copied from Record Books of The Ohio Fuel Oil Co. by C. E. Krebs
Nov. 14, 1911.

No location
Fanned

	Top.	Bottom.	Thickness.
Sand	10	- 50	40
Slate	50	- 85	35
Pittsburgh Sand (water at 90')	85	- 190	105
Slate	190	- 310	120
Sand	310	- 330	20
Slate	330	- 390	60
Lime	390	- 420	30
Slate	420	- 496	76
Sand	496	- 526	30
Slate	526	- 540	14
Lime	540	- 552	12
Sand	552	- 560	8
Lime	560	- 590	30
Big Dunkard Sand	590	- 608	18
Slate	608	- 611	3
Sand	611	- 670	59
Slate	670	- 692	22
Sand	692	- 713	21
Slate	713	- 736	23
Sand	736	- 785	49
Slate	785	- 791	6
Sand	791	- 814	23
Slate and shells	814	- 858	44
Sand	858	- 923	65
Slate	923	- 960	37
Lime	960	- 997	37
Slate	997	- 1060	63
Black lime	1060	- 1122	62
Slate	1122	- 1180	58
Little Salt Sand	1180	- 1229	49
Slate	1229	- 1248	19
Salt Sand (gas, 1280'; show of oil, 1292'; little water, 1330'; big water, 1379')	1248	- 1555	107
Slate	1555	- 1560	5
Maxton Sand	1560	- 1575	15
Little Lime	1575	- 1598	23
Slate	1598	- 1603	5
Pencil Cave	1603	- 1613	10
Big Lime	1613	- 1747	34
Slate and shells	1775	- 2107	332
Berea Grit	2107		
Slate and shells	2107	- 2254	147
Total depth		2254	