

70223

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced Aug. 2, 1910, and completed Aug. 8, 1910.

Drilling commenced Aug. 15, 1910 and completed Oct. 24, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers: Ed. Rumminger and S. S. Ferrell.

Conductor, 16'.

When drilled in this well was turned over to the United Fuel Gas Co. who tubed and packed it. They furnished tubing, packer, and other fittings.

Examined and approved by E. H. Lange, Foreman.

Record copied from Record Books of The Ohio Fuel Oil Co.,
by C. E. Krebs, Nov. 11, 1911.

	Top.	Bottom.	Thickness.
Conductor	0	- 16	16
Slate and shells	16	- 20	4
Sand	20	- 190	170
White slate	190	- 245	55
Red rock	245	- 275	30
Sand	275	- 600	325
Red rock and shells	600	- 635	35
Little and Big Dunkard Sands	635	- 710	75
Slate	710	- 890	180
Sand	890	- 910	20
(show of gas, 910-930')			
Black shale	930	- 988	58
Sand	988	- 1013	25
Black slate and shells	1013	- 1040	27
Sand	1040	- 1130	90
Slate and shells	1130	- 1180	50
Sand	1180	- 1215	35
Lime	1215	- 1260	45
Slate and shells	1260	- 1340	80
Little Salt Sand	1340	- 1442	102
Slate	1442	- 1464	22
Salt Sand	1464	- 1505	41
(oil and gas, 1505-1540')			
Slate	1540	- 1555	15
Sand	1555	- 1560	5
(little water, 1560-1660')			
(hole full water, 1660-1690')			
Slate	1690	- 1780	90
Black lime	1780	- 1788	8
Maxton Sand	1788	- 1818	30
Slate	1818	- 1840	22
Little Lime	1840	- 1845	5
Red rock	1845	- 1860	15
Lime	1860	- 1866	6
Sandy lime	1866	- 1886	20
Pencil Cave	1886	- 1900	14
Broken Big Lime	1900	- 1918	18
Second Pencil, cave			
Red rock	1918	- 1954	36
Broken lime	1954	- 1969	15
Big Lime	1969	- 1975	6
Big Injun Sand (gas, 2012')	1975	- 2012	37
Total depth			2025

Walton District, Roane County, W. Va.

By The Ohio Fuel Oil Co.

Rig commenced Aug. 2, 1910, and completed Aug. 8, 1910.

Drilling commenced Aug. 15, 1910 and completed Oct. 24, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers: Ed. Rumminger and S. S. Ferrell.

Conductor, 16'.

When drilled in this well was turned over to the United Fuel Gas Co. who tubed and packed it. They furnished tubing, packer, and other fittings.

Examined and approved by E. H. Lange, Foreman.

Record copied from Record Books of The Ohio Fuel Oil Co.,

by C. E. Krebs, Nov. 11, 1911.

	Top.	Bottom.	Thickness.
Conductor	0 -	16	16
Slate and shells	16 -	20	4
Sand	20 -	190	170
White slate	190 -	245	55
Red rock	245 -	275	30
Sand	275 -	600	325
Red rock and shells	600 -	635	35
Little and Big Dunkard Sands	635 -	710	75
Slate	710 -	890	180
Sand	890 -	910	20
(show of gas, 910-930')			
Black shale	930 -	988	58
Sand	988 -	1013	25
Black slate and shells	1013 -	1040	27
Sand	1040 -	1130	90
Slate and shells	1130 -	1180	50
Sand	1180 -	1215	35
Lime	1215 -	1260	45
Slate and shells	1260 -	1340	80
Little Salt Sand	1340 -	1442	102
Slate	1442 -	1464	22
Salt Sand	1464 -	1505	41
(oil and gas, 1505-1540')			
Slate	1540 -	1555	15
Sand	1555 -	1560	5
(little water, 1560-1660')			
(hole full watery 1660-1690')			
Slate	1690 -	1780	90
Black lime	1780 -	1788	8
Maxton Sand	1788 -	1818	30
Slate	1818 -	1840	22
Little Lime	1840 -	1845	5
Red rock	1845 -	1860	15
Lime	1860 -	1866	6
Sandy lime	1866 -	1886	20
Pencil Cave	1886 -	1900	14
Broken Big Lime	1900 -	1918	18
Second Pencil, cave			
Red rock	1918 -	1954	36
Broken lime	1954 -	1969	15
Big Lime	1969 -	1975	6
Big Injun Sand (gas, 2012')	1975 -	2012	37
Total depth			2025