



ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

COALQUEST DEVELOPMENT, LLC

Coal Operator or Owner
100 TYGART DRIVE, GRAFTON, WV 26354
Address

COALQUEST DEVELOPMENT, LLC

Coal Operator or Owner
100 TYGART DRIVE, GRAFTON, WV 26354
Address

JOHN & JANET KIMBREW

Lease or Property Owner
2 SHENANDOAH DRIVE, FAIRMONT, WV 26554
Address

ICG TYGART VALLEY, LLC

Name of Well Operator
100 TYGART DRIVE, GRAFTON, WV 26354

Complete Address

THORNTON (638)

Well Location

KNOTTSVILLE

District

TAYLOR

County

1557

Well No.

COLLINS, RUTH STURM

Farm

STATE INSPECTOR SUPERVISING PLUGGING *Delbert Moore*

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by ICG Tygart Valley, LLC well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 12th day of September, 2016 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Removed 4177' of 1 1/2" tubing from Surface to 4177'. Tripped in hole with 2 3/8" drill pipe and tagged solid plug at 5260'. Cemented bottom hole plug from 5260' to 2594' with 165 sacks of Expandable Cement with Gas Blocker additive. Removed 1890' of 4 1/2" casing from Surface to 1890'. Left an unknown amount of 4 1/2" casing in the hole from 1890' to an unknown depth. Remaining 4 1/2" casing has preexisting perforations at the following depths: 5200', 4168' and 3404'. Cleaned 7 7/8" hole from Surface to 1890'. Tagged top of 4 1/2" casing at 1890'. Reduced hole to 3 3/4". Cleaned 3 3/4" hole from 1890' to 2594'. Tagged top of the bottom hole plug at 2594'. Cemented intermediate plug from 2594' to 1101' with 240 sacks of Expandable Cement. Section milled 26' of 8 5/8" casing from 685' to 711' due to extreme bond. Section milled 8 5/8" casing through the Lower Kittanning Coal seam from 696' to 701'. Left 1208' of 8 5/8" casing in the hole from Surface to 1234'. Tagged intermediate plug with 7 7/8" bit at 1101'. Left 20' of 16" conductor casing in the hole from Surface to 20'.	16" Conductor Casing 8 5/8" Casing 4 1/2" Casing 1 1/2" Tubing	0' Milled 26' 1890' 4177'	20' 1208' Unknown 0'	
Cemented hole from 1101' back to Surface as follows: From 1101' to 496' with 180 sacks of Thixotropic Cement with green dye. From 496' back to the Surface with 185 sacks of Expandable Cement. Cement did circulate at the Surface.				
Coal Seams	Description of Monument			
<u>LOWER KITTANNING</u>	77" of 7" casing w/company name, well number,			
(Name)	permit number and date cemented stated on 7"			
(Name)	casing. Well marker will be attached to the			
(Name)	cement plug at ground level.			

... And that the work of plugging and filling said well was completed on the 29th day of September, 2016

And further deponents saith not.

Delbert Moore
Delbert Moore


Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 11th day of Oct 2016

Carol A. Mayb
Notary Public

My commission expires: 9-12-17

Permit No. 47-91-00474-P
Well No. 1557



OKD