

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

COALQUEST DEVELOPMENT, LLC  
Coal Operator or Owner  
2708 CRANBERRY SQUARE MORGANTOWN, WV 26508  
Address

COALQUEST DEVELOPMENT, LLC  
Coal Operator or Owner  
2708 CRANBERRY SQUARE MORGANTOWN, WV 26508  
Address

CHARLES AND BETTY J. GOUGH  
Lease or Property Owner  
RR 2, BOX 140, KEYSER, WV 26726  
Address

ICG TYGART VALLEY, LLC  
Name of Well Operator  
100 TYGART DRIVE, GRAFTON, WV 26354  
Complete Address

GRAFTON (378)  
Well Location  
KNOTTSVILLE  
District

TAYLOR  
County

GOUGH 1  
Well No.

GOUGH, CHARLES & BETTY J.  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *Ernest Reynolds*  
AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by ICG Tygart Valley, LLC well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 25<sup>th</sup> day of July, 2016 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Tripped in hole with 2 3/8" drill pipe and tagged solid plug at 5127'. Cemented bottom hole plug from 5127' to 2571' with 335 sacks of Expandable Cement with Gas Blocker additive. Removed 2550' of 4 1/2" casing from Surface to 2550'. Left 2557' of 4 1/2" casing in the hole from 2550' to 5107'. Remaining 4 1/2" casing has preexisting perforations at the following depths: 4874', 4274' and 4022'. Cleaned 7 7/8" hole from Surface to 2550'. Tagged top of 4 1/2" casing at 2550'. Tripped in hole with 2 3/8" drill pipe to 2571'. Tagged top of bottom hole plug at 2571'. Cemented intermediate plug from 2571' to 1020' with 425 sacks of Expandable Cement. Section milled 38' of 8 5/8" casing from 510' to 548'. Section milled 8 5/8" casing through the Lower Kittanning Coal seam from 521' to 527'. Left 1064' of 8 5/8" casing in the hole from Surface to 1102'. Left 5' of 16" conductor casing in the hole from Surface to 5'.				
<b>Cemented hole from 1020' back to Surface as follows:</b> From 1020' to 321' with 210 sacks of Thixotropic Cement with green dye. From 321' back to the Surface with 80 sacks of Expandable Cement. Cement did circulate at the Surface.				
Coal Seams	Description of Monument			
<u>LOWER KITTANNING</u>	77" of 7" casing w/company name, well number,			
(Name)	permit number and date cemented stated on 7"			
(Name)	casing. Well marker will be attached to the			
(Name)	cement plug at ground level.			

... And that the work of plugging and filling said well was completed on the 5<sup>th</sup> day of August, 2016

And further deponents saith not.

*Delbert Moore*  
Delbert Moore

*Kevin S. Wright*  
Kevin S. Wright

Sworn to and subscribed before me this 29<sup>th</sup> day of August, 2016

*Thomas J. Sullivan*  
Notary Public

My commission expires: 08/16/17

Permit No. 47-91-00609-P  
Well No. GOUGH 1

