



WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Way 279  
Wayne Quad

Company  
Address  
Farm  
Location  
Well No  
District  
Surface  
Oil & Gas

The Owens, Libbey-Owens Gas Dept.  
P.O. Box 2111, Charleston, 28, W.Va. 8 1/2  
Hoard-Baldwin Acres 179  
Camp Creek  
657 Elev. 621.2  
Stonewall Wayne  
Andrew Fry, E. Lynn, W.Va.

Gas Well  
CASING & TUBING

	204	Same
6 5/8	1127'	1127'
3	926	926
2	1847	1847
3/4	1837	1837

Commenced  
Completed  
Date shot

The Owens, Libbey-Owens, Gas Dept.  
Box 2111, Charleston, 28, W.Va.  
March 24, 1943  
May 13, 1943

Anchor Wall Packer  
Size 3 x 6 5/8 x 16"  
Depth 1844-1860

Volume  
Rock Pressure  
Fresh Water  
Salt Water

5-12-43 2327 to 2790  
5-12-43 1258 to 1293  
with 4,450# & 350# Detonite  
229,000 C.F.  
Injun 325#; Shale 273# 50 hrs.  
53' H.F.  
743' H.F.

Perf. top 2725  
Perf. bot 2748  
Perf. top 2748  
Perf. bot 2769

Coal at 118' 24"

Sand	Lt	S	0	20	Slate & Shell	Gr	S	2189	2240
Gravel	Lt	S	20	25	Slate	Dk	S	2240	2284
Slate	Dk	S	25	39	Slate & Shells	Dk	S	2284	2330
Gravel	Gr	S	39	44	Shale	Br	S	2330	2427
Sand & Gravel	Lt	S	44	69	Slate & Shells	Gr	S	2427	2461
Sand	Lt	H	69	108	Shale	Br	S	2461	2594
Slate	Dk	S	108	118	Shale & Shells	Br	S	2594	2551
Coal	Bk	S	118	120	Shale	Br	S	2651	2784
Slate	Gr	S	120	144	Slate	Dk	S	2784	2804
Sand	Lt	S	144	165	Slate	Wh	S	2804	2962
Slate	Gr	S	165	176	Slate & Shells	Wh	S	2962	2992
Sand	Wh	S	176	212	Shale	Wh	S	2992	3012
Slate	Wh	S	212	419	Shale	Br	S	3012	3072
Sand	Gr	S	419	464	Corniferous	Gr	H	3072	3085
Slate	Gr	S	464	548	TOTAL DEPTH				3085
Sand	Wh	S	548	594					
Slate	Dk	S	594	624	Gas 2340'	7,000	Increase		
Sand	Wh	S	624	931	Gas 2471	5,000	"		
Slate	Lt	S	931	941	Gas 2651	2,000	"		
Sand	Lt	S	941	988	Gas 2713	3,000	"		
Slate	Wh	S	988	992	Gas 3072'	2,000	"		
Sand	Wh	H	992	996					
Red Rock		S	996	1000					
Slate	Gr	S	1000	1023					
Lime	Dk	H	1023	1052					
Lime	Wh	H	1052	1062					
Slate	Wh	S	1062	1064					
Big Lime	Wh	H	1064	1093					
Big Lime	Wh	H	1093	1127					
Big Lime	Wh	H	1127	1138	Oil 1132 1/2 bail pr. hr.				
Big Lime	Wh	H	1138	1220					
Injun Sand	Gr	H	1220	1227					
Injun Sand	R	S	1227	1247					
Injun Sand	Gr	H	1247	1259					
Injun Sand	Gr	S	1259	1291	Gas 1266-80' 146,000 C.F.				
Injun Sand	Gr	H	1291	1298					
Slate & Shells	Gr	S	1298	1510					
Slate & Shells	Gr	S	1510	1689					
Slate	Wh	S	1689	1724					
Shell	Gr	H	1724	1796					
Slate	Dk	S	1796	1821					
Berea Sand	Gr	H	1821	1840	Gas 1825' Increase 10,000				
Slate	Wh	S	1840	1843					
Sand	Gr	H	1843	1877					
Slate & Shells	Gr	S	1877	1907					
Shale	Br	S	1907	1972					
Slate & Shell	Gr	S	1972	2142					
Shell	Gr	H	2142	2162					
Slate	Dk	S	2162	2189					

3072  
621  
2451