

LATITUDE 39 42 30

03 22 08

LONGITUDE

0.555
1.72W
15' 10C

7'5 OGIS topo location

7.5' loc	<u>0.555</u>	15' loc	<u>3.43S</u>
	<u>1.72W</u>	(calc.)	<u>3.94W</u>

Company _____

Farm _____

Quad Hundred Mannington NC

County _____

District Church

WELL LOCATION MAP

File No. Well 36

Church District, Wetzel County, W. Va.

By Kingston Corporation, Pittsburgh, Pa. (802 Grant Bldg.)

On 23.25 acres; surface owned by Maude Six et al., Hundred, W.Va.,
and minerals by Kingston Corporation, Pittsburgh, Pa.

Drilled under permit Wet-36, issued Sept. 22, 1930.

Elevation, 1608' B.

13' conductor; 10" casing, 300'; 8 1/4", 1807'; 6", 2587'.

No packer. Casing not perforated. No liners used.

Coal was encountered at 1387-1392'.

Nov. 9, 1931.

Completion reported to Dept. of Mines Dec. 30, 1930 & Jan. 12, 1931. and/
Well was not shot. Drilled deeper Oct. 13 to Nov. 1, 1931, by Duquesne

Gas well. /// Gas Corp., 225 Washington Trust Bldg., Washington, Pa.

Record to RCT from Mrs. Griffith Aug. 30, 1938.

	Top.	Bottom.	Thickness.
✓ Pittsburgh Coal (water, 5 bailers 24 hrs.)	1387-1392		5
✓ Big Dunkard Sand	1908 - 1974		66
✓ Gas Sand	2085 - 2120		35
✓ Salt Sand	2195 - 2285		90
✓ 2nd Salt Sand	2343 - 2415		72
✓ Maxton Sand	2505 - 2540		35
✓ Big Lime (gas)	2575 - 2661		86
Total depth of drilling (Big Injun Sand)	2671		
DRILLED DEEPER:			
✓ Big Injun Sand (gas, 180,000 cu. ft.)	2671 - 2885		214
✓ 30-Ft. shells or Murraysville Sand	3195 - 3220		25
✓ Gantz Sand	3325 - 3376		51
✓ 50-Ft. Sand	3378 - 3450		72
✓ Gordon Stray Sand	3470 - 3495		25
✓ Gordon Sand	3525 - 3594		69
✓ Fifth Sand	3616 - 3639		23
Total depth	3645		

30115
2671
974