

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOL PENNSYLVANIA COAL COMPANY
Coal Operator or Owner
1000 CONSOL ENERGY DRIVE, CANONSBURG, PA 15317
Address
CONSOL PENNSYLVANIA COAL COMPANY
Coal Operator or Owner
1000 CONSOL ENERGY DRIVE, CANONSBURG, PA 15317
Address
DAVID AND LINDSEY KERR
Lease or Property Owner
2211 VERMONT ROUTE 128, WESTFORD, VT 05494
Address

LEATHERWOOD, INC.
Name of Well Operator
1000 CONSOL ENERGY DRIVE, CANONSBURG, PA 15317
Complete Address
HUNDRED, WV 7.5
Well Location
CHURCH
District
WETZEL
County
5401
Well No.
HENRY HIMELRICK
Farm

RECEIVED
Office of Oil and Gas

STATE INSPECTOR SUPERVISING PLUGGING _____

AFFIDAVIT

MAR 21 2016

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

WV Department of
Environmental Protection

DAVID HARMAN and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by CONSOLIDATION COAL COMPANY well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 9th day of December, 2015 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In	
Removed 2605' to 3 1/2" casing from Surface to 2605' with extreme difficulty. Left an unknown amount of 3 1/2" casing in the hole from 2605' to an unknown depth. Cemented bottom hole plug from 2605' to 2261' with 70 sacks of Expandable Cement. Removed 1564' of 7" casing from Surface to 1564'. Left 800' of 7" casing in the hole from 1564' to 2364'. Cut remaining 7" casing at the following depths: 2252', 2165', 2055', 1949', 1862', 1760', and 1652'. Cemented from 2261' to 1415' with 150 sacks of Expandable Cement. Removed 1262' of 8 5/8" casing from Surface to 1262'. Left 253' of 8 5/8" casing in the hole from 1262' to 1515'. Cut remaining 8 5/8" casing at the following depth: 1407'. Cleaned 9 7/8" hole from Surface to 1262'. Cleaned 9 7/8" hole through the Waynesburg Coal seam from 821' to 827', the Sewickley Coal seam from 1078' to 1082', and the Pittsburgh Coal seam from 1183' to 1190'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1262' to 1415'. Tagged cement plug at 1415'. Left 325' of 10 3/4" casing in the hole from Surface to 325'. Left 20' of 16" conductor casing in the hole from Surface to 20'.		16" Conductor	0'	20'	
			10 3/4"	0'	325'
			8 5/8"	1262'	253'
			7"	1564'	800'
			3 1/2"	2605'	Unknown
Cemented hole from 1415' back to Surface as follows: From 1415' back to the Surface with 440 sacks of Expandable Cement. Cement did circulate at the Surface.					
Coal Seams	Description of Monument				
<u>WAYNESBURG COAL</u>	821' to 827'	77" of 7" casing w/company name, well number,			
<u>SEWICKLEY COAL</u>	1078' to 1082'	permit number and date cemented stated on 7"			
<u>PITTSBURGH COAL</u>	1183' to 1190'	casing. Well marker will be attached to the			
(Name)		cement plug at ground level.			

... And that the work of plugging and filling said well was completed on the 28th day of December, 2015

And further deponents saith not.

David Harman
David Harman

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 18th day of Feb 2016

Carol A. Mayle
Notary Public

My commission expires: 9-12-17



Permit No. 47-103-00062-P
Well No. 5401

03/25/2016