

LATITUDE 39 42 30

80 47 30

LONGITUDE

0 → OGIS  
7.5' loc

0 → wet,  
38

7.5 OGIS topo location

7.5' loc	<u>0.925</u>	15' loc	<u>3.805</u>
	<u>1.78W</u>	(calc.)	<u>4.60W</u>

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad New Martinsville ±15' NE

County \_\_\_\_\_

District Proctor

WELL LOCATION MAP

File No. Wet. 80

Proctor District, Wetzel County, W. Va.  
 By Valley Run Oil & Gas Co., Cameron, W. Va.  
 On 155 acres, surface owned by Clarence Gudy and Monroe Heirs,  
 Proctor, W. Va., and minerals by Gudy-Monroe Heirs, Proctor, W. Va.  
 Drilled under permit Wet-80, issued.....  
 Elevation, 1274.07' L.  
 10" casing, 160'; 8", 1380'; 6", 2150'; 2" tubing, 2838'.  
 Anchor packer, 5' 10" long, set at 2880'.  
 Coal was encountered at 350', 479-485, 789-785, 805-807, and 894-899'.  
 Well was shot at 2861 to 2862'.  
 Gas well. Record to RCT from Mrs. Griffith Sept. 2, 1938.  
 Completion reported to Dept. of Mines Aug. 1, 1935.

	Top.	Bottom.	Thickness.
Native coal, black, soft	350	- ...	..
Slate and shells, soft	350	- 479	129
Coal blossom, black, soft	479	- 485	6
Slate and shells, soft	480	- 650	170
Slate, dark, hard	650	- 665	15
Lime shells, and slate, soft	665	- 720	55
Limestone, hard	720	- 730	60
Coal blossom, black, soft	730	- 735	5
Limestone, hard	785	- 805	20
Coal blossom, soft	805	- 807	2
Lime, hard	807	- 880	73
Slate, hard	880	- 894	14
Pittsburgh Coal, black, soft	894	- 899	5
Slate and shells, soft	899	- 925	26
Sand, soft	925	- 950	25
Red rock, soft	950	- 1115	165
Lime, hard	1115	- 1140	25
Slate and shell, soft	1140	- 1213	73
Sand, soft	1213	- 1223	10
Slate and shell, soft	1223	- 1285	62
Little Dunkard Sand, hard	1285	- 1305	20
Slate and shell, soft	1305	- 1365	60
Big Dunkard Sand, hard	1365	- 1380	15
Slate, dark, hard	1380	- 1385	5
Red rock, soft	1385	- 1392	7
Slate and shell, soft	1392	- 1455	63
Gas sand, soft	1455	- 1495	40
Slate and shells, soft	1495	- 1635	140
Salt Sand, soft (water)	1635	- 1685	50
Slate and shell, soft	1685	- 1729	44
Sand, soft	1729	- 1770	41
Slate and shells, soft	1770	- 1910	140
Sand, soft	1910	- 1945	35
Slate and shells, soft	1945	- 2008	63
Big Lime, soft	2008	- 2100	92
Big Injun Sand, hard	2100	- 2102	2
Sand, soft (water) (Big Injun)	2102	- 2230	128
Sand, soft (Big Injun)	2230	- 2250	20
Slate and shell, soft	2250	- 2400	150
Sand, soft	2400	- 2450	50
Slate and shells, soft	2450	- 2640	190
Sand, soft	2640	- 2660	20
Slate, hard	2660	- 2665	5
Pink rock, soft	2665	- 2700	35
Slate and shells, soft	2700	- 2858	158
Gordon Sand, soft (gas pay, soft, 2860-2862')	2858	- 2880	22