


LATITUDE

394230

802730

LONGITUDE



7.5 OGIS topo location

7.5' loc 1.50S
1.11W

15' loc 4.38S
 (calc.) 3.33W

KLA 12/6/89

Company _____

Farm _____

Quad Hundred (403) Mannington NW

County _____

District Church

WELL LOCATION MAP

File No. Wetzel 136



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Maunington

WELL RECORD
WELL TO BE ABANDONED

Oil or Gas Well Dry
(KIND)

Permit No. WET-136-D

Company Carnegie Natural Gas Company
Address 1015 Frick Building, Pittsburgh, Pa.
Farm H. Kennedy Acres 68
Location (waters) Fish Creek
Well No. 2E-1508 Elev. 1030
District Church County Putnam
The surface of tract is owned in fee by Heirs of H. Kennedy,
Howard H. Kennedy, Address Hundred, W. Va.
Attorney-in-fact
Mineral rights are owned by Heirs of H. Kennedy,
Howard H. Kennedy, Address Hundred, W. Va.
Drilling commenced March 18, 1952 (deeper)
Drilling completed April 6, 1952 (deeper)
Date Shot From _____ To _____
With _____

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
18			Kind of Packer
13			
10			Size of
8 1/2			
6 1/2			Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

Open Flow /10ths Water in Dry Inch
/10ths Merc. in _____ Inch
Volume _____ Cu. Ft.
Rock Pressure _____ lbs. _____ hrs.
Oil _____ bbls., 1st 24 hrs.
Fresh water _____ feet _____ feet
Salt water _____ feet _____ feet

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____
COAL WAS ENCOUNTERED AT _____ FEET _____ INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Commenced drilling deeper at			750'				
Line	White	Hard	750	760'			
Slate	White	Soft	760	767			
Line	White	Hard	767	770			
Red Rock	Red	Hard	770	773			
Line	Light	Hard	773	787			
Red Rock	Red	Hard	787	789			
Slate	Light	Soft	789	792			
Pink Rock	Light	Hard	792	803			
Line	Light	Hard	803	806			
Pink Rock	Light	Hard	806	810			
Line	Light	Hard	810	814			
Red Rock	Red	Soft	814	825			
Slate	Gray	Soft	825	829			
Line	Light	Hard	829	831			
Pink Rock	Light	Soft	831	833			
Line	Gray	Hard	833	853			
Red Rock	Red	Soft	853	864			
Red Rock	Red	Hard	864	895			
Line	Dark	Hard	895	902			
Red Rock	Red	Hard	902	915			
Line	Dark	Hard	915	924			
Red Rock	Red	Hard	924	933			
Line	Light	Hard	933	938			
Line	Light	Soft	938	946			
Red Rock	Red	Soft	946	954			
Line	Gray	Hard	954	960			
Line	Dark	Soft	960	964			
Line	Dark	Hard	966	970			
Pink Rock	Light	Hard	970	975			
Line	Gray	Hard	975	982			
Pink Rock	Light	Soft	982	1006			
Red Rock	Red	Soft	1006	1019			
Pink Rock	Light	Soft	1019	1058			
Total Depth	Steel Line			1058'			

© Dan, Res
2E-1508



JAN 19 1953

H. KENNEDY 2E-1508 WET 136 D

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

W E L L R E C O R D

Permit No. Wat-136

Gas Well

Company	-	Carnegie Natl. Gas Co.	<u>CASING & TUBING</u>	<u>PACKER</u>
Address	-	Pittsburgh, Penna.		
Farm	-	N. Kennedy. Acres- 68	8 $\frac{1}{4}$ 182'-8"	Kind- Anchor
Location(Waters)	-	Fish Creek	6-5/8 662'-6"	Size- 6-5/8" x3"
Well No.	-	2 - 1508 . Elev. 1030'	3 750'	Depth-697' to 699'
District	-	Church. County- Wetzel	Opening.	Perf.top- 720'
Surface	-	N. Kennedy		Perf.Bot- 750'
Address	-	Hundred, W. Va.		
Mineral	-	same	Coal was encountered at 390' 620'	
Drilling	-	Commenced- 12/2/36	& 730'	
		Completed- 12/21/36		
Date Shot	-			
Open Flow	-	58/10ths water in 1"		
Rock Press.	-	38 lbs. in 24 hrs.		
Oil	-			
Fresh Water	-	2-6" bailers per hr.		
		390' to 395'		
Salt Water	-			

*reval
April 5'2*

Formation Color ^H or Top Bottom Results				Formation Color ^H or Top Bottom Results			
Clay	Light	S	0	15			
Sand	White	H	15	30			
Slate	Dark	S	30	55			
Mud	Red	S	55	62			
Slate	Dark	S	62	70			
Mud	Grey	S	70	95			
Lime	White	H	95	120			
Slate	Dark	S	120	128			
Rock	Red	S	128	132			
Lime	White	H	132	148			
Slate	Dark	S	148	165			
Lime	White	H	165	175			
Slate	Dark	S	175	194			
Lime	White	H	194	200			
Slate	Dark	S	200	212			
Sand	White	H	212	220			
Slate	Dark	S	220	268			
Coal	Black	S	268	270			
Lime	White	S	270	310			
Slate	Dark	S	310	340			
Lime	White	H	340	390			
Coal	Black	S	390	395	Water	390'-395'	2-6" Bailers per hr.
Lime	White	H	395	420			(Waynesburg)
Slate	Grey	S	420	440			
Lime	White	H	440	472			
Slate	Dark	S	472	480			
Lime	White	H	480	495			
Slate	Dark	S	495	500			
Lime	White	H	500	515			
Shale	White	S	515	520			
Lime	White	H	520	615			
Slate	Dark	S	615	620			
Coal	Black	S	620	622	Mapletown		
Slate	Dark	S	622	648			
Lime	White	H	648	683			
Slate	Dark	S	683	690			
Lime	White	H	690	705			
Slate	Dark	S	705	730			
Coal	Black	S	730	738	Pittsburgh		
Lime	White	H	738	743			
Slate	Dark	S	743	745			
Sand	White	H	745	750			
Total Depth				750			