



west virginia department of environmental protection

Office of Oil and Gas
601 57th Street SE
Charleston, WV 25304
(304) 926-0450
(304) 926-0452 fax

Earl Ray Tomblin, Governor
Randy C. Huffman, Cabinet Secretary
www.dep.wv.gov

August 29, 2013

WELL WORK PERMIT
Horizontal 6A Well

This permit, API Well Number: 47-10302920, issued to STONE ENERGY CORPORATION, is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Please be advised that form WR-35, Well Operators Report of Well Work is to be submitted to this office within 90 days completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

In addition to the applicable requirements of this permit, and the statutes and rules governing oil and gas activity in WV, this permit may contain specific conditions which must be followed. Permit conditions are attached to this cover letter.

Per 35CSR-4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926-0499 ext. 1654.

James Martin
Chief

Operator's Well No: HOWELL 8H-R
Farm Name: HOWELL, CHARLES AND RUTH
API Well Number: 47-10302920
Permit Type: Horizontal 6A Well
Date Issued: 08/29/2013

Promoting a healthy environment.

PERMIT CONDITIONS

West Virginia Code § 22-6A-8(d) allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. Failure to adhere to the specified permit conditions may result in enforcement action.

CONDITIONS

1. If the operator encounters an unanticipated void, or an anticipated void at an unanticipated depth, the operator shall notify the inspector within 24 hours. Modifications to the casing program may be necessary to comply with W. Va. Code § 22-6A-5a (12), which requires drilling to a minimum depth of thirty feet below the bottom of the void, and installing a minimum of twenty (20) feet of casing. Under no circumstance should the operator drill more than fifty (50) feet below the bottom of the void or install less than twenty (20) feet of casing below the bottom of the void.
2. When compacting fills, each lift before compaction shall not be more than 12 inches in height, and the fill material shall be within plus or minus 2% (unless soil test results show a greater range of moisture content is appropriate and 95% compaction can still be achieved) of the optimum moisture content as determined by the standard proctor density test, ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort. Each lift must meet 95 % compaction of the optimum density based on results from the standard proctor density test of the actual soils used in specific engineered fill sites. Each lift shall be tested for compaction, with a minimum of two tests per lift per acre of fill. All test results shall be maintained on site and available for review.
3. Operator shall install signage per § 22-6A-8g (6) (B) at all source water locations included in their approved water management plan within 24 hours of water management plan activation.
4. Oil and gas water supply wells will be registered with the Office of Oil and Gas and all such wells will be constructed and plugged in accordance with the standards of the Bureau for Public Health set forth in its Legislative rule entitled *Water Well Regulations*, 64 C.S.R. 19. Operator is to contact the Bureau of Public Health regarding permit requirements. In lieu of plugging, the operator may transfer the well to the surface owner upon agreement of the parties. All drinking water wells within fifteen hundred feet of the water supply well shall be flow tested by the operator upon request of the drinking well owner prior to operating the water supply well.
5. Pursuant to the requirements pertaining to the sampling of domestic water supply wells/springs the operator shall, no later than thirty (30) days after receipt of analytical data provide a written copy to the Chief and any of the users who may have requested such analyses.
6. If any explosion or other accident causing loss of life or serious personal injury occurs in or about a well or well work on a well, the well operator or its contractor shall give notice, stating the particulars of the explosion or accident, to the oil and gas inspector and the Chief, within 24 hours of said accident.
7. During the casing and cementing process, in the event cement does not return to the surface, the oil and gas inspector shall be notified within 24 hours.

103-02920

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS
WELL WORK PERMIT APPLICATION

103 5 554

1) Well Operator: STONE ENERGY CORPORATION 494490923 Wetzel Green Porters Falls
Operator ID County District Quadrangle

2) Operator's Well Number: HOWELL #8H-R Well Pad Name: HOWELL

3 Elevation, current ground: 1342' Elevation, proposed post-construction: 1300'

4) Well Type: (a) Gas Oil Underground Storage

Other REPLACEMENT WELL

(b) If Gas: Shallow Deep
Horizontal

5) Existing Pad? Yes or No: YES

DMH
6-17-17

6) Proposed Target Formation(s), Depth(s), Anticipated Thicknesses and Associated Pressure(s):
Proposed target formation is the Marcellus Shale @ 6,885' TVD (-5,585' Sea Level), thickness is 56', and approximate rock pressure will range between 3,800 and 4,400 psig

7) Proposed Total Vertical Depth: 6,930' TVD

8) Formation at Total Vertical Depth: Marcellus Shale

9) Proposed Total Measured Depth: 13,500'

10) Approximate Fresh Water Strata Depths: 75' Shallowest and 1056' Deepest

11) Method to Determine Fresh Water Depth: Depth of bit when water shows in the flowline or when drilling soap is injected

12) Approximate Saltwater Depths: 1,740'

13) Approximate Coal Seam Depths: 1,051

14) Approximate Depth to Possible Void (coal mine, karst, other): None Anticipated

15) Does proposed well location contain coal seams directly overlying or adjacent to an active mine? If so, indicate name and depth of mine: No

16) Describe proposed well work: Existing well site. MIRU conductor rig and set conductor into solid rock cementing to surface. RDMO conductor rig and MIRU top-hole rig and drill to KOP while setting surface and intermediate casing string and cementing them to surface. RDMO top-rig and MIRU horizontal rig. Drill curve and lateral on WBM, set production casing and cement in place. RDMO.

17) Describe fracturing/stimulating methods in detail:
MIRU completion equipment. Clean out well bore and run CBL from approximately 30 degrees in the curve to surface. Perforate 24 individual stages in the lateral section of the well bore and stimulate each individual set of perforations using slick water and sand. MIRU service rig and flow well back. Clean out well bore and run production tubing. Test well flow. See the attached frac chemical addendum for additives used during the stimulation.

18) Total area to be disturbed, including roads, stockpile area, pits, etc, (acres): EXISTING - 16.15 ACRES

19) Area to be disturbed for well pad only, less access road (acres): EXISTING - 9.81 ACRES

103-02420

20)

CASING AND TUBING PROGRAM

TYPE	Size	New or Used	Grade	Weight per ft.	FOOTAGE: For Drilling	INTERVALS: Left in Well	CEMENT: Fill -up (Cu. Ft.)
Conductor	20"	New	LS	94.0	40'	40'	20 - GTS
Fresh Water	13.375"	New	J55	54.5	1,290'	1,290'	1,178 - CTS
Coal	13.375"	New	J55	54.5	1,290'	1,290'	1,178 - CTS
Intermediate	9.625"	New	J55	36.0	2,450'	2,450'	655 Lead - 321 Tail CTS
Production	5.5"	New	P110	20.0		13,500'	1,100 Lead - 2,263 Tail TOC @ 1,450'
Tubing	2.375"	New	J55	4.7		6,700'	N/A
Liners							

Fresh Water/Coal string will be set above sea level (-1300').

DMH
6-17-12

TYPE	Size	Wellbore Diameter	Wall Thickness	Burst Pressure	Cement Type	Cement Yield
Conductor	20"	24"	0.375"	N/A	Type 1	1.18
Fresh Water	13.375"	17.5"	0.380"	2,730 psi	Class A	1.19
Coal	13.375"	17.5"	0.380"	2,730 psi	Class A	1.19
Intermediate	9.625"	12.25"	0.352"	3,520 psi	Class A	1.26 Lead - 1.19 Tail
Production	5.5"	8.75"	0.361"	12,360 psi	Class A	1.25 Lead - 1.23 Tail
Tubing	2.375"	N/A	0.190"	7,700 psi	N/A	N/A
Liners	N/A					

PACKERS

Kind:	N/A			
Sizes:				
Depths Set:				

Received
Office of Oil & Gas

JUL 19 2013

103-02920

WW - 6B
(3/13)

21) Describe centralizer placement for each casing string.

spring centralizers with one (1) being placed above the guide shoe and one (1) every second joint to surface, 21 total.

-Intermediate string will incorporate bow spring centralizers with one (1) above the guide shoe, one (1) above float collar, and one (1) every third joint to surface for a total of 22 centralizers. One straight vane rigid centralizer will be placed as close to the surface as practical.

-Production string will incorporate alternating left and right hand spiral centralizers with one (1) every fourth joint to 500' above KOP and every third joint from KOP to top of slant for a total 70 left/right rigid spiral centralizers. From top of slant to TOC bow spring centralizers will be used on every third joint for a total of 10.

22) Describe all cement additives associated with each cement type.

-Fresh Water/Coal string uses a slurry of Class A cement with 0.125 pps Cello Flake, 1.0% CaCl₂, and 0.2% Anti-Foam

-Intermediate string uses a Lead/Tail slurry. Lead is Class A cement with 0.2 gps Accelerator, 0.08 gps Dispersant, 0.1 gps Anti Foam, 4.0% Expanding Agent, and 0.5% Gas Migration Agent. Tail is Class A cement with 1.0% CaCl₂, 0.125 pps Cello Flake, and 0.2% Anti-Foam.

- Production string uses a Lead/Tail slurry. the Lead is Class A cement with 4.0% Expanding Agent, 0.5% Gas Migration Agent, 0.25 gps Dispersant, 0.1 gps Anti-foam, and 0.06 gps Retarder. The Tail is Class A cement with 0.2% Dispersant, 0.4% Fluid Loss, 0.2% Anti-Foam, 0.15% retarder, and 0.2% Anti-Settling Agent.

23) Proposed borehole conditioning procedures.

-Fresh Water/Coal section will be conditioned by circulating air down the down the drill string at TD for 30 to 90 minutes or until the well bore clears of cuttings.

- Intermediate section will conditioned by circulating air and/or stiff foam through the drill string at TD for 30 to 120 minutes until well bore clears of cuttings.

-Production section will be conditioned by circulating drilling fluid through the drill string at TD for 120 to 720 minutes until cuttings shakers clear of cuttings.

*Note: Attach additional sheets as needed.

DAH
6-17-13

Received
Office of Oil & Gas

103-02920



WW-9 ADDENDUM

Drilling Medium Anticipated for This well

- Vertical section of well bore, down to KOP, will be drilled on air and/or a combination of air and drilling soap.
- From KOP through the curve section and horizontal section of well bore will be drilled on a brine-water based mud system.

Additives to be Used While Drilling

- Common additives when air drilling: KCl (CAS No. 1302-78-9 & 14808-60-7), soda ash (CAS No. 497-19-8), shale stabilizer (CAS No 67-48-1 & 7732-1835), drilling soap (CAS No. 111-76-2), air hammer/motor lubricant.
- Common water based additives for mud drilling: NaCl (CAS No. 7647-14-5), KCl (CAS No. 7447-40-7), barite (CAS No. 13462-86-7 & 14808-60-7), starch (CAS No. 9005-25-8), PAC (CAS No. 9004-32-4), xanthum gum (CAS No. 11138-66-2), PHPA (CAS No. 64742-47-8), polysaccharide (CAS No. 11138-66-2), sulfonated asphaltic material (CAS No. 269-212-0 & 238-878-4), aluminum silicate (CAS No. 37287-16-4), gilsonite (CAS No. 12002-43-6), graphite (CAS No.14808-60-7 & 7782-42-5), shale stabilizer (CAS No. 67-48-1 & 7732-18-5), fluid loss control polymers (CAS No. 9004-34-6), viscosity control polymers (CAS No. 11138-66-2 & 107-22-2), soda ash (CAS No. 497-19-8), sodium bicarbonate (CAS No. 144-55-8), NaOH (CAS No. 1310-73-2, 7647-14-5, & 7732-18-5), lime (CAS No. 1305-62-0), gypsum (CAS No.778-18-9) , citric acid (CAS No. 77-92-9), biocide (CAS No. 52-51-7 or 7732-18-5 + 67-56-1 + 141-43-5), CaCO₃ (CAS No. 471-34-1) , cellulose fibers (CAS No. 14808-60-7), nut plug (CAS No. 9004-34-6 & 14808-60-7), cross-linking polymers (CAS No. 107-22-2 & 11138-66-2), other LCMs, surfactants (CAS No. 64-17-5) , ROP enhancer/lubricant (CAS No. 8002-13-9), beads, corrosion inhibitor (CAS No. 7732-18-5), aluminum stearate (CAS No. 300-92-5), defoamer (CAS No. 246-771-9).

MSDS are available upon request.

DMH
6-17-13

Received
Office of Oil & Gas

103-02920



WW-9 ADDENDUM

Drill Cuttings Disposal Method

- Closed loop drilling system will be incorporated. No waste pits will be constructed. All drill cuttings are put through a drier system and hauled to and disposed of at approved and permitted landfills.

Landfills or Offsite Names and Permit Numbers

Wetzel County Sanitary Landfill
Rt. 1, Box 156A
New Martinsville, WV 26155
SWF-1021 / WV01909185

Brooke County Sanitary Landfill
Colliers, WV 26035
SWF-1013 / WV0109029

Dmit
6-17-13

Received
Office of Oil & Gas

JUN 19 2013

Well: **Howell 8H-R**
 State: **West Virginia**
 County: **Wetzel**
 District: **Green**
 Prospect: **Mary**
 Location: Surface: North = 4,382,902 East = 517,671 (UTM NAD 83)
 PBHL: North = 4,381,369 East = 518,970 (UTM NAD 83)
 PTD: 13500' MD / 6930' TVD

STONE ENERGY - PROPOSED HORIZONTAL

Revision: 4-June-13

Permit Number: 47-103-0
 Permit Issued: [Redacted]
 as Built Ground Elevation: 1300'
 Kelly Bushing: 18'
 Rig:
 Spud Date:
 TD Date:
 Rig Release Date:

Received
 Office of Oil & Gas
 JUN 19 2013


HOLE SIZE	PILOT HOLE FORMATION TOPS	WELLBORE DIAGRAM	CASING & CEMENTING DATA DIRECTIONAL DATA	MW & FLUID TYPE	HOLE DEV.	
24" Hole then Driven	40' KB (22' BGL)		CONDUCTOR PIPE 20" x 3/8" wall L/S PE @ 40' (set in bedrock & grouted to surface)		Vertical	
17-1/2" Hole	Shallowest FW 75' TVD Pittsburgh Coal 1051' TVD Deepest FW 1056' TVD 1290' TVD		SURFACE CASING 13-3/8" 54.5# J-55 STC @ 1290' MD/TVD Set through fresh water zones Set through coal zones Cemented to surface	Air / Mist	Vertical	
12-1/4" Hole	Salt Water 1740' TVD Little Lime 2144' TVD Big Lime 2174' TVD Big Injun Sandstone 2244' TVD Base of Big Injun 2294' TVD 2450' TVD		INTERMEDIATE CASING 9-5/8" 36.0# J-55 LTC @ 2450' MD/TVD Set through potential salt water zones Set below base of Big Injun Cemented to surface	Stiff Foam	Vertical	
8-3/4" Hole	Berea Sandstone 2826' TVD Gordon Sandstone 3018' TVD Rhinstreet Shale 5844' TVD			Air / Dust	Slant	
8-3/4" Hole	Cashaqua Shale 6584' TVD Middlesex Shale 6720' TVD West River Shale 6738' TVD Geneseo Shale 6808' TVD Tully Limestone 6831' TVD Hamilton Shale 6857' TVD		KOP @ 6213' TVD		WBM in Curve	
8-3/4" Hole in Lateral	Marcellus Shale 6903' TVD				WBM in Lateral	~90°
	Onondaga Limestone 6952' TVD					
			Landing Point (LP) @ 7538' MD / 6930' TVD ~90° angle ~147° azimuth			
				TD @ 13500' MD / 6930' TVD PRODUCTION CASING 5-1/2" 20.0# P-110 CDC @ 13500' MD Top of Cement @ 1450' (~1000' inside 9-5/8")		

Notes: Formation tops as per vertical pilot hole
 Curve & lateral tops will vary due to structural changes
 Directional plan based upon best estimate of structure

DMIT
6-17-13

103-02920

NOTE: THIS DRAWING IS NOT TO SCALE. THE DIMENSIONS REFLECTED ON THE DRAWING ARE ESTIMATED MEASUREMENTS AND FOR REFERENCE ONLY.



© 2010 Weatherford International Inc. All rights reserved

Customer: STONE ENERGY

Project: 46705

Quote: 99565 v 3

Tender, Project or Well: 2011- 2012 CONVENTIONAL MARCELLUS

Date: 07-17-2011

Drawn By: RF

103-02920

WW-9
(5/13)

Page _____ of _____
API Number 47 - 103 - _____
Operator's Well No. _____ HOWELL #8H-R

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS

FLUIDS/ CUTTINGS DISPOSAL & RECLAMATION PLAN

Operator Name STONE ENERGY CORPORATION OP Code 494490923
Watershed (HUC 10) Fishing Creek Quadrangle Porters Falls
Elevation 1300' County Wetzel District Green

Do you anticipate using more than 5,000 bbls of water to complete the proposed well work? Yes No

Will a pit be used for drill cuttings? Yes No

If so, please describe anticipated pit waste: N/A

Will a synthetic liner be used in the pit? Yes No If so, what ml.? N/A

Proposed Disposal Method For Treated Pit Wastes:

- Land Application
 - Underground Injection (UIC Permit Number Hunter Disposal 2D0859721, 34-121-24037, 34-121-24086)
 - Reuse (at API Number Flow Back will be collected and used for other stimulations, wells not permitted yet)
- Off Site Disposal (Supply form WW-9 for disposal location)
- Other (Explain _____)

Will closed loop system be used? Both the Top-Hole Rig and Horizontal Rig will incorporate the use of a closed loop system

Drilling medium anticipated for this well? Air, freshwater, oil based, etc. Top-Hole on air and/or drilling soap, Horizontal on Salt Brine

-If oil based, what type? Synthetic, petroleum, etc. N/A

Additives to be used in drilling medium? See WW-9 Addendum

DMH
6-17-13

Drill cuttings disposal method? Leave in pit, landfill, removed offsite, etc. All cuttings to be disposed of in an approved landfill

-If left in pit and plan to solidify what medium will be used? (cement, lime, sawdust) N/A

-Landfill or offsite name/permit number? Wetzel County Sanitary Landfill (SWF-1021/WW109185)

I certify that I understand and agree to the terms and conditions of the GENERAL WATER POLLUTION PERMIT issued on August 1, 2005, by the Office of Oil and Gas of the West Virginia Department of Environmental Protection. I understand that the provisions of the permit are enforceable by law. Violations of any term or condition of the general permit and/or other applicable law or regulation can lead to enforcement action.


I certify under penalty of law that I have personally examined and am familiar with the information submitted on this application form and all attachments thereto and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine or imprisonment.

Office of Oil & Gas

Company Official Signature [Signature]
Company Official (Typed Name) Timothy P. McGregor
Company Official Title Land Coordinator

Subscribed and sworn before me this 11th day of June, 20 13

[Signature]
My commission expires 5/18/2021



103-02920

Form WW-9

Operator's Well No. HOWELL #8H-R

STONE ENERGY CORPORATION

Proposed Revegetation Treatment: Acres Disturbed 16.15 Prevegetation pH _____

Lime 2.0 Tons/acre or to correct to pH 6.5

Fertilizer (10-20-20 or equivalent) 500-750 lbs/acre (500 lbs minimum)

Mulch 0.50 to 0.75 + Straw Tons/acre

Seed Mixtures

Area I		Area II	
Seed Type	lbs/acre	Seed Type	lbs/acre
Marcellus Mix	100.0	Marcellus Mix	100.0
White or Ladino Clover	10.0	White or Ladino Clover	10.0
Orchard Grass	40.0	Orchard Grass	40.0
Winter Rye	50.0	Winter Rye	50.0

Attach:
Drawing(s) of road, location, pit and proposed area for land application.
Photocopied section of involved 7.5' topographic sheet.

Plan Approved by: [Signature]

Comments: _____

Title: Oil + Gas Inspector

Date: 6-17-17

Received
Office of Oil & Gas

Field Reviewed? () Yes () No



103-02920

STONE ENERGY CORPORATION

Addendum for

Planned Additives to be Used in Fracturing or Stimulations

Listed below are the chemicals used in addition to water and sand (CAS-No 14808-60-7) and their respective quantities for slick water fracturing;

- 0.5 gal/thousand gallons of water – Friction Reducer (CAS-No 7783-20-2)
- 0.25 gal/thousand gallons of water – Bacteria Control (CAS-No 11-30-8)
- 0.25 gal/thousand gallons of water – Clay Stabilizer (CAS- No 75-57-0)
- 0.75 gal/thousand gallons of water – Surfactant (CAS-No Proprietary)
- 0.25 gal/thousand gallons of water – Scale Inhibitor (CAS-No 7601-54-9 & 107-21-1)
- 2000 gal of 15% HCl (CAS-No 7647-01-0) per stage with/ 2 gal/thousand gallons of acid Corrosion Inhibitor (CAS-No 67-56-1, 107-19-7, & Proprietary) and 6 pints/thousand gallons of acid – Iron Stabilizer (CAS-No 6381-77-7)
- A 15 lb. Linear Gel and breaker is sometimes used during a stage but the exact amount is not known until the stimulation is in progress (CAS-No Proprietary & 7727-54-0)

Dmit
6-17-13

Received
Office of Oil & Gas



Water Management Plan: Primary Water Sources



WMP-01357

API/ID Number: 047-103-02920

Operator:

Stone Energy Corporation

Howell 8H-R

Important:

For each proposed primary water source (including source intakes for purchased water sources) identified in your water management plan, and summarized herein, DEP has made an evaluation concerning water availability over the specified date range. DEP's assessment is based on the following considerations:

- Statistical analysis of historical USGS stream gauge data (transferred to un-gauged locations as necessary);
- Identification of sensitive aquatic life (endangered species, mussels, etc.);
- Quantification of known existing demands on the water supply (Large Quantity Users);
- Minimum flows required by the Army Corps of Engineers; and
- Designated stream uses.

Based on these factors, DEP has provided, for each intake location (and origination point for purchased water), a reference gauge location and discharge flow reading which must be surpassed prior to withdrawals. Additionally, DEP has established a minimum passby flow at the withdrawal location which must also be surpassed prior to withdrawals. These thresholds are considered terms of the permit and are enforceable as such.

DEP is aware that some intake points will be used for multiple wells and well sites. In these cases, the thresholds set by the Water Management Plan are to be interpreted as total withdrawal limits for each location over the specified date range regardless of how many wells are supported by that intake.

For all purchased water intakes, determinations of water availability are made at the original source intake location. It is the responsibility of the Oil and Gas Operator, not the seller, to cease withdrawal of water from the seller when flows are less than the minimum gauge reading at the stream gauge referenced by the Water Management Plan in order to protect stream uses.

Note that the determinations made herein are based on the best available data, but it is impossible to predict water availability in the future. While the DEP has carefully established these minimum withdrawal thresholds, it remains the operator's responsibility to protect aquatic life at all times. Approval to withdrawal is contingent upon permission from the land owner. It is the responsibility of the operator to secure and maintain permission prior to any withdrawals.

The operator is reminded that 24-48 hours prior to withdrawing (or purchasing) water, DEP must be notified by email at DEP.water.use@wv.gov.

APPROVED AUG 21 2013

Source Summary

WMP-01357

API Number:

047-103-02920

Operator:

Stone Energy Corporation

Howell 8H-R

Stream/River

Source **Fishing Creek @ Tuttle** Wetzel Owner: **Eugene Wells Tuttle**

Start Date	End Date	Total Volume (gal)	Max. daily purchase (gal)	Intake Latitude:	Intake Longitude:
6/1/2013	6/1/2014	2,700,000		39.590278	-80.780833

Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV

Max. Pump rate (gpm): **694** Min. Gauge Reading (cfs): **69.05** Min. Passby (cfs) **23.06**

DEP Comments:

Source **Little Fishing Creek @ Conley** Wetzel Owner: **Ronald Gene Conley**

Start Date	End Date	Total Volume (gal)	Max. daily purchase (gal)	Intake Latitude:	Intake Longitude:
6/1/2013	6/1/2014	4,100,000		39.608922	-80.79156

Regulated Stream? Ref. Gauge ID: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV

Max. Pump rate (gpm): **972** Min. Gauge Reading (cfs): **69.67** Min. Passby (cfs) **5.54**

DEP Comments:

Source Detail

WMP-01357

API/ID Number: 047-103-02920

Operator: Stone Energy Corporation

Howell 8H-R

Source ID: 20589 Source Name Fishing Creek @ Tuttle
Eugene Wells Tuttle

Source Latitude: 39.590278
Source Longitude: -80.780833

HUC-8 Code: 5030201

Drainage Area (sq. mi.): 156.46 County: Wetzel

Anticipated withdrawal start date: 6/1/2013

Anticipated withdrawal end date: 6/1/2014

- Endangered Species? Mussel Stream?
- Trout Stream? Tier 3?
- Regulated Stream?
- Proximate PSD?
- Gauged Stream?

Total Volume from Source (gal): 2,700,000

Max. Pump rate (gpm): 694

Max. Simultaneous Trucks: 0

Max. Truck pump rate (gpm): 0


Reference Gaug 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV

Drainage Area (sq. mi.) 458.00

Gauge Threshold (cfs): 45

Month	Median monthly flow (cfs)	Threshold (+ pump)	Estimated Available water (cfs)
1	167.79	24.61	143.26
2	211.06	24.61	186.53
3	236.17	24.61	211.63
4	175.37	24.61	150.84
5	92.51	24.61	67.98
6	32.31	24.61	7.77
7	18.28	24.61	-6.25
8	15.05	24.61	-9.48
9	7.71	24.61	-16.82
10	9.69	24.61	-14.85
11	47.30	24.61	22.77
12	115.58	24.61	91.04

Water Availability Profile



Water Availability Assessment of Location

Base Threshold (cfs): 15.37
 Upstream Demand (cfs): 0.00
 Downstream Demand (cfs): 0.00
 Pump rate (cfs): 1.55
 Headwater Safety (cfs): 3.84
 Ungauged Stream Safety (cfs): 3.84

Min. Gauge Reading (cfs): 69.05
 Passby at Location (cfs): 23.06

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

Source Detail

WMP-01357

API/ID Number: 047-103-02920

Operator: Stone Energy Corporation

Howell 8H-R

Source ID: 20591 Source Name: Little Fishing Creek @ Conley
 Ronald Gene Conley

Source Latitude: 39.608922

Source Longitude: -80.79156

HUC-8 Code: 5030201

Drainage Area (sq. mi.): 37.52 County: Wetzel

Anticipated withdrawal start date: 6/1/2013

Anticipated withdrawal end date: 6/1/2014

Total Volume from Source (gal): 4,100,000

Max. Pump rate (gpm): 972

Max. Simultaneous Trucks: 0

Max. Truck pump rate (gpm): 0

Endangered Species? Mussel Stream?

Trout Stream? Tier 3?

Regulated Stream?

Proximate PSD?

Gauged Stream?


Reference Gaug: 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV

Drainage Area (sq. mi.): 458.00

Gauge Threshold (cfs): 45

Month	Median monthly flow (cfs)	Threshold (+ pump)	Estimated Available water (cfs)
1	40.24	7.70	32.63
2	50.61	7.70	43.00
3	56.63	7.70	49.03
4	42.06	7.70	34.45
5	22.18	7.70	14.58
6	7.75	7.70	0.14
7	4.38	7.70	-3.22
8	3.61	7.70	-4.00
9	1.85	7.70	-5.76
10	2.32	7.70	-5.29
11	11.34	7.70	3.73
12	27.72	7.70	20.11

Water Availability Profile



Water Availability Assessment of Location

Base Threshold (cfs): 3.69

Upstream Demand (cfs): 0.00

Downstream Demand (cfs): 0.00

Pump rate (cfs): 2.17

Headwater Safety (cfs): 0.92

Ungauged Stream Safety (cfs): 0.92

Min. Gauge Reading (cfs): 69.67

Passby at Location (cfs): 5.53

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.



Water Management Plan: Secondary Water Sources



WMP- 01357

API/ID Number | 047-103-02920

Operator:

Stone Energy Corporation

Howell 8H-R

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Multi-site impoundment

Source ID:	20592	Source Name	Tuttle Fresh Water Impoundment		Source start date:	6/1/2013
					Source end date:	6/1/2014
	Source Lat:	39.586528	Source Long:	-80.779889	County	Wetzel
	Max. Daily Purchase (gal)		Total Volume from Source (gal):			2,700,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-588

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 20593	Source Name	Conley Fresh Water Impoundment		Source start date:	6/1/2013
				Source end date:	6/1/2014
	Source Lat:	39.608922	Source Long:	-80.79156	County
					Wetzel
	Max. Daily Purchase (gal)		Total Volume from Source (gal):		4,100,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.


Reference: WMP-589

Recycled Frac Water

Source ID: 20594	Source Name	Maury Pad; Weekley Pad		Source start date:	6/1/2013
				Source end date:	6/1/2014
	Source Lat:		Source Long:		County
	Max. Daily Purchase (gal)		Total Volume from Source (gal):		487,200


DEP Comments:

Plot spotted 103-02920



DmH
6-11-17

NOTES:
 1. USGS TOPOGRAPHIC MAP:
 PORTERS FALLS 7.5' USGS QUADRANGLES
 2. ALL COORDINATES SHOWN ARE IN WV STATE PLANE-
 NORTH (NAD 83) WV83-NF



HRG
 Herbert, Rowland & Grubic, Inc.
 Engineering & Related Services

240 Scott Avenue, Suite 1
 Morgantown, WV 26508
 (304) 284-9222
 Fax (304) 284-9223
 hrg@hrg-inc.com
 www.hrg-inc.com

**WATER / WELL LOCATION MAP
 FOR
 HOWELL WELL PAD SURFACE HOLE 8H**


GREEN DISTRICT WETZEL COUNTY WEST VIRGINIA

PROJ. MGR. - THK
DESIGN - MAN
CADD - MAN
CHECKED - RJW
SCALE - 1" = 2000'
DATE - MAY 2011


DRAWING NO. WL-08
SHEET NO. 8 OF 10
PROJECT P005461.0461

File Name: C:\CH01\3D\Projects\005461_0461\Drawn_Sett\DWG\005461.0461.dwg Layer: 0 DB NL -08 May 25, 2011 - P. Mann cadsw@hr.com

HOWELL #8H-R



I, THE UNDERSIGNED, HEREBY CERTIFY THAT THIS PLAT IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF AND SHOWS ALL THE INFORMATION REQUIRED BY LAW AND THE REGULATIONS ISSUED AND PRESCRIBED BY THE DIVISION OF ENVIRONMENTAL PROTECTION.



(+) DENOTES LOCATION OF WELL ON UNITED STATES TOPOGRAPHIC MAPS.
DATE MAY 30, 20 13
OPERATORS WELL NO. HOWELL #8H-R
API WELL NO. 47-103-02920
STATE COUNTY WV WVA

P.S. 834
Doyle Hupp Jr.
HUPP Surveying & Mapping
P.O. Box 647 Grantsville, WV 26147
(304) 354-7035 EMAIL: hupp@frontiernet.net

MINIMUM DEGREE OF ACCURACY 1/2500 FILE NO. W2208 (BK 64-54)
PROVEN SOURCE OF ELEVATION SG-GPS(OPUS) SCALE 1" = 1000'

STATE OF WEST VIRGINIA
DIVISION OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS

WELL TYPE : OIL GAS LIQUID INJECTION WASTE DISPOSAL IF "GAS" PRODUCTION STORAGE DEEP SHALLOW

LOCATION : ELEVATION 1342' WATERSHED FISHING CREEK
DISTRICT GREEN COUNTY WETZEL QUADRANGLE PORTERS FALLS 7.5'
SURFACE OWNER CHARLES & RUTH HOWELL ACREAGE 51±
ROYALTY OWNER CHARLES & RUTH HOWELL, et al LEASE ACREAGE 629.81±
PROPOSED WORK : LEASE NO. _____
DRILL CONVERT DRILL DEEPER REDRILL FRACTURE OR STIMULATE PLUG OFF OLD FORMATION PERFORATE NEW FORMATION PLUG AND ABANDON CLEAN OUT AND REPLUG OTHER _____
PHYSICAL CHANGE IN WELL (SPECIFY) _____ TARGET FORMATION MARCELLUS
ESTIMATED DEPTH TVD 6,930' MD 13,500'

WELL OPERATOR STONE ENERGY CORPORATION DESIGNATED AGENT TIM MCGREGOR
ADDRESS P.O. BOX 52807 LAFAYETTE, LA 70308 ADDRESS 6000 HAMPTON CENTER SUITE B MORGANTOWN WV 26505

LONGITUDE 80°47'30" — 10,720'
LAT. 39°35'44.1" — 10,720'