



AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL COMPANY
Lease or Property Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
WALLACE 7.5'
Well Location
GRANT
District
WETZEL
County
7108
Well No.
CONSOLIDATION COAL COMPANY
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]*

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MICHAEL MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 22nd day of March, 2017 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
	Cleaned hole with 12 1/4" bit from Surface to 443'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 443' to 605', top of 8 5/8" casing. Cleaned out 8 5/8" casing from 605' to 1,630'. Removed 8 5/8" casing from 605' to 1,474'. Casing was parted from 906' to 1,134'. Made attempt to remove remaining casing, pulled in excess of 150% of string weight. Left 8 5/8" casing in well from 1,474' to 1,722'. (Casing depth based on State issued Well Record). Cleaned 9 7/8" hole from 605' to 1,474'. Cleaned 9 7/8" hole through Pittsburgh Coal Seam from 1,214' to 1,220.5'. Tagged plug with 7 7/8" bit at 1,630'.	8 5/8"	822'	248'
		20"	0'	19'
	<u>Cemented hole from 1,630' back to Surface as follows:</u> From 1,630' to 1,420' with 60 sacks of Expandable Cement. From 1,420' to 1,097' with 210 sacks of Thixotropic Cement with dye. From 1,097' back to Surface with 615 sacks of Expandable Cement. A total of 885 sacks of cement was used to plug hole to surface. Cement did circulate at the surface. Left 19' of 20" Conductor Casing in the well from Surface to 19'.			
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(1,214' - 1,220.5')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 12th day of April, 2017.

And further deponents saith not.

Michael P. Mitchell
Michael Mitchell
Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 15th day of May 2017

Carol A. Mayle
Notary Public

My commission expires: 9-12-17



Permit No. 47-103-03179-P
Well No. 7108

RECEIVED
Office of Oil and Gas

MAY 25 2017

05/26/2017
WV Department of
Environmental Protection