

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

COASTAL FOREST RESOURCES COMPANY
Lease or Property Owner
P. O. BOX 709, BUCKHANNON, WV 26201
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address

FOLSOM, WV 7.5'
Well Location

GRANT
District

WETZEL
County

7226
Well No.

ANSON M. CAIN
Farm

STATE INSPECTOR SUPERVISING PLUGGING 

AFFIDAVIT


STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 2nd day of May, 2017 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 12 1/2' hole from Surface to 378'. Reduced to 9 7/8". Cleaned 9 7/8" hole from 378' to 559'. Removed all 42' of 8 5/8" casing from 559' to 601'. Cleaned 9 7/8" hole from 559' to 921', including through the Pittsburgh Coal Seam from 681' to 688'. Cleaned 7 7/8" hole from 921' to 944'. Cleaned 6 1/4" hole from 944' to 987'. Tagged bottom of hole at 987'.		8 5/8" Casing 16" Conductor	42' 0'	0' 10'
<u>Cemented hole from 987' back to Surface as follows:</u> Cemented bottom hole from 987' back to 888' with 50 sacks of Expandable Cement. Cemented hole from 888' to 581' with 220 sacks of Thixotropic Cement with green dye. Cemented hole from 581' to Surface with 370 sacks of Expandable Cement. Cement did circulate at Surface. A total of 640 sacks was used to Cement Wellbore. Left 10' of 16" Conductor Casing in the hole from 10' to Surface.				
Coal Seams		Description of Monument		
Pittsburgh	(681' - 688')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 12th day of May, 2017.

And further deponents saith not.


Delbert Moore


Kevin S. Wright

Sworn to and subscribed before me this 30th day of May, 2017


Notary Public



Permit No. 47-103-03182-P
Well No. 7226