

Church District, Wetzel County, W. Va.

By The Pure Oil Co.

Well completed Sept. 1, 1903.

One string of tools left in hole--1 rope socket, 1 -9-ft. sinker, 1 set jars, 1 - 80-ft. stem and bit, and 1 - 20-ft. bailer. Drilled by tools and could not find top of sand. Bailer in beside tools. Top of tools, 2270 ft. Well measured when tubed 2304 ft. Well filled up 800 ft. 1st screw in 2nd pay.

Drilled by Fisher Oil Co.

From bottom of casing to top of Maxton Sand, 108 feet.

Well pulled out March, 1905.

3 1/2" Conductor, 14'; 10" casing, 363' (300' pulled); 8", 1583' (900' pulled); 6-5/8", 2197' (1700' pulled). Report mailed to Pittsburgh 3-16-1905.

Shot Sept. 23, 1903, by C. C. Fisher, with 80 qts.; 2nd pay, 10' shell; 21' anchor between shells; depth top of shot, 2nd pay, 2362'; 1st pay, 6' shell; depth top of shot, 2335', 1st pay.

Shot Jan. 14, 1905, by Fisher Torpedo Co., with 70 qts.; dump shot, dumped at 2290 ft.; no good.

Record from E. Townley, Room 2308, 35 E. Wacker Drive, Chicago, Ill., March 13, 1931.

	Top.	Bottom.
Pittsburgh Coal	1190	
Gas Sand	1833	1958
Salt Sand	2022	2090
2nd Salt Sand	2155	2205
Red cave	2264	2305
Maxton Sand	2305	2377
(1st pay, 2339-2342'; 2nd pay, 2365-2370')		
Total depth		2377