No. 354 O.F.-Wetzel.

	NOT FOUND
Ohnrah Mintrict, Wetzel County, W. Va.	
By Pure Oil Co.	30967
Well started July 3, 1906; completed, Aug. 1, 190	
Contractor, Schaffner Bros.	
10" dasing, 182' (pulled); 82", 1512' (pulled); 6	§*, 2060*,
Shot Aug. 3, 1906, by Fisher Torpedo Co., with 80	gts., 20% shell,
13' ancher; depth of well when shot, 2261';	iepth top of shot,
2222 Production, good.	
Shot Aug. 30, 1906, by Tisher Torpedo Co., with 1	
15 anchor; depth of well when shot, 2260;	depth top of shot.
2223; production, bridged.	
Shot Aug. 17. 1906, by Fisher Torpedo Co., with 1	20 qts.; 30° sheel;
anchor, 10, 17, 24, 28; t depth of well when	shot, 2268; depth
top of shot, 2222'; production, bridged.	
Drilled deeper July 12, 1909, at 2285.	
Filled up 135' within 30 hours. (Maxton).	
Record from E. Townley, Room 2308, 35 E. Wacker D.	rive, Chicago, Ill.,
March 13, 1931.	
	_
Top. Bot	tom,

	Top. Bottom.
Pittsburgh Coal	1080 - 1088
Salt Sand (1900')	1090 - 2075
	2109 - 2196
Red cave	ST() - ST)0
Maxton Sand (pay sand, 2225-2227';	
pay sand, 2236-2241; pay sand,	
2252 -2257°)	2196
Total depth	2269
DRILLED DESPER July 12, 1909:	
Big Lime	2285 - 2370
Big Injun Sand	2370 - 2575
50-Pt. Sand	3020 - 3060
30-Ft. Sand	3081 - 3121
Stray Sand	3125 - 3141
Gordon Sand	3162 - 3195
Fourth Sand	3218 - 3285
Slate	3285 - 3305
5th Send shell	3305 - 3309
Slate	3309 - 3314
Total depth	3314