

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS

FEB 03 2017

AFFIDAVIT OF PLUGGING AND FILLING WELL

WV Department of
Environmental Protection

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Cabot Corporation Operator Well No.: 7239

LOCATION: Elevation: 823.1 ft (250.9 m) Quadrangle: Rockport, WV
District: Steele County: Wood
Latitude: 2295 Feet South of 39 Deg. 4 Min. 00 Sec.
Longitude: 1078 Feet West of 81 Deg. 33 Min. 30 Sec.

Well Type: OIL _____ GAS ^{X (storage)} _____

Company Columbia Gas Transmission, LLC Coal Operator not operated
1700 MacCorkle Ave SE or Owner _____
Charleston, WV 25325-1273 _____
Agent Paul Amick Coal Operator _____
Permit Issued Date 8/3/2016 or Owner _____

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of Wood ss:

James Amos and Steven Simmons being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well say that said work was commenced on the 9 day of November, 2016, and the well was plugged and filled in the following manner:

TYPE	FROM	TO	PIPE REMOVED	LEFT
cement	surface	25'	none	16", 10-3/4", 8-5/8", 7" and 3-1/2"
cement	25'	1310'	none	10-3/4", 8-5/8", 7" and 3-1/2"
cement	1310'	2182'	none	8-5/8", 7" and 3-1/2"
cement	2182'	4958'	none	7" and 3-1/2"
cement	4958'	5126'	none	3-1/2"

Description of monument: steel plate installed on top of 7" casing with API tack welded and that the work of plugging and filling said well was completed on the 14 day of December, 2016.

* Refer to post P&A wellbore diagram

And further deponents saith not. James E Amos

Sworn and subscribe before me this 5th day of January, 2017

My commission expires: 5-17-2017

Notary Public

Affidavit reviewed by the Office of Oil and Gas: [Signature]

Title: 2-2-16

03/31/2017

ROCKPORT 7239

(12/20/2016)

Post P&A

** not to scale **

RECEIVED
Office of Oil and Gas

FEB 03 2017

WV Department of
Environmental Protection

Uncovered tops of all casing strings and
verified they had been cemented to surface

16" csg @ 25'
- no record of cement

13-3/8" csg ran/pulled
(csg seat @ 789')

10-3/4" csg @ 1310'
(CBL indicates cemented to surface)

Salt Sand 1708 - 2028' (elog depth)

8-5/8" csg @ 2182'
(CBL indicates cemented to surface)

Berea 2368 - 2371' (elog depth)

CBL indicates
gap in cement
2920 - 3148 ft

Light gray
represents
cement installed
prior to P&A

Perforated @ 3061' and attempted to squeeze
cemented - no fluid movement through
perfs. Covered perfs with cement.

Dark gray is new
cement installed
during P&A

* Note no driller's record of
gas, oil, or water shows,
except for in Oriskany.

Mechanical bridge plug @ 4915 ft

Marcellus 4911 - 4927' (elog depth)

Onondaga Ls 4927 - 5042'
(elog depth)

Oriskany 5042 - 5088' (elog depth)
gas storage - drillers show @ 5046'
Helderberg Ls 5088 - 5126'

7" 23# csg @ 4958'
(depth based on Dmag log response)

Parmaco wall &
anchor packer @
4998'

TD 5126'

3-1/2" 9.2# tbg @ 5126' - slotted anchor on bottom

03/31/2017