



New Location
 Drill Deeper
 Abandonment

Map N30 S8 W48

Company	South Penn Oil Co.
Address	Parkersburg, West Virginia
Farm	J. Lee Taylor
Tract	Acres 650 Lease No. S.D.-3
Well (Farm) No.	1 Serial No.
Elevation (Spirit Level)	808.39 Ground
Quadrangle	Parkersburg - SE
County	Wood District Williams
Engineer	Wm. A. Hayes
Engineer's Registration No.	1422
File No.	Drawing No.
Date	Aug. 21, 1953 Scale 1" = 400'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP

FILE NO. W00-406

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

Samples 8-E (4549-4790')

3-0 308
 Deep Well



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION 7

Parkersburg

WELL RECORD

Permit No. W00-406

Oil or Gas Well Dry

(KIND)

Company South Penn Oil Company
Address Union Trust Building, Parkersburg, W. Va.
Farm J. Lee Taylor Acres 650
Location (waters) Pond Run and Plum Run of Ohio River
Well No. 1 Elev 808.39
District Williams County Wood
The surface of tract is owned in fee by O. C. Haught, Exr. et al
R. D. #1, Salem Address West Virginia
Mineral rights are owned by O. C. Haught, Exr. et al
R. D. #1, Salem Address West Virginia
Drilling commenced November 12, 1953
Drilling completed February 20, 1954
Date Shot From To
With
Open Flow /10ths Water in Inch
/10ths Merc. in Inch
Volume None Cu. Ft.
Rock Pressure lbs. hrs.
Oil None bbls., 1st 24 hrs.
Fresh water feet feet
Salt water 1040 feet 1608 feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16	20	20	
18-3/8	504		
10-3/4	1111	1111	Size of
8-5/8	1788		
XX 7	4725		Depth set
5 3/16			
8			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED SIZE No. Ft. Date

COAL WAS ENCOUNTERED AT FEET INCHES
FEET INCHES FEET INCHES
FEET INCHES FEET INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Red Clay			0	120			
Red Rock			120	180			
Lime			180	195			
Red Rock			195	200			
White Slate			200	216			
Lime			216	245			
Red Rock			245	260			
Lime			260	272			
White Slate			272	300			
Sand			300	307			
Slate			307	353			
Red Rock			353	360			
Lime			360	370			
Red Rock			370	375			
Lime			375	400			
Red Rock			400	416			
Lime			416	440			
Red Rock			440	450			
Slate			450	465			
Sand			465	480			
Slate			480	535			
Red Rock			535	545			
White Slate			545	620			
Sand			620	655			
White Slate			655	675			
Red Rock			675	777			
White Slate			777	785			
Red Rock			785	795			
Slate			795	840			
Lime			840	864			
Slate			864	870			
Red Rock			870	890			
White Slate			890	930			
Sand		Hard	930	953			
Sand	Dark		953	970			
Gritty Lime			970	990			
Sand			990	1087	Water	1040	2 Bailers per hr
Slate & Shells			1087	1150	Oil	1065	Very light show
Lime	Light		1150	1163			



