



MINIMUM ERROR OF CLOSURE 1' in 200

SOURCE OF ELEVATION Well No 1 Sherman Dils Jr. Wood Permit  
No 542 Elev. 616.8

New Location  Drill Deeper  Abandonment

"I, THE UNDERSIGNED, HEREBY CERTIFY THAT THIS MAP IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF AND SHOWS ALL THE INFORMATION REQUIRED BY PARAGRAPH 6 OF THE RULES AND REGULATIONS OF THE OIL AND GAS SECTION OF THE MINING LAWS OF WEST VIRGINIA."

Company Resorts Development Corp  
 Address 401-27th St. Vienna, W. Va.  
 Farm Paul Rawlings  
 Tract 4.4 Acres 180' ± Lease No. \_\_\_\_\_  
 Well (Farm) No. one Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 645.7  
 Quadrangle Parkersburg F.C.  
 County Wood District Williams  
 Engineer [Signature]  
 Engineer's Registration No. 2492  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date April 6, 1967 Scale 1" = 100'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. WOOD-554

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



RECEIVED  
JUL 10 1972

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
Oil and Gas Division  
WELL RECORD

OIL & GAS DIVISION  
DEPT. OF MINES

Quadrangle Petersburg  
Permit No. W00554

Rotary \_\_\_\_\_ Oil   
Cable  Gas   
Recycling \_\_\_\_\_ Comb.   
Water Flood \_\_\_\_\_ Storage \_\_\_\_\_  
Disposal \_\_\_\_\_ (Kind) \_\_\_\_\_

Company REDUITS DEVELOPMENT CORP  
Address 401 27 ST VIENNA WVA  
Farm PAUL RAWLINGS Acres 26  
Location (waters) OHIO RIVER  
Well No. 1 Elev. 549  
District WILLIAMS County WOOD  
The surface of tract is owned in fee by PAUL RAWLINGS  
Address CENTRAL WVA  
Mineral rights are owned by PAUL RAWLINGS  
Address SAME  
Drilling Commenced JUNE 1967  
Drilling Completed JULY 1967  
Initial open flow 700,000 cu. ft. 10 bbls.  
Final production 40,000 cu. ft. per day 7 bbls.  
Well open 24 hrs. before test \_\_\_\_\_ RP.

Casing and Tubing	Used in Drilling	Left in Well	Cement fill up Cu. ft. (Sks.)
Size 20-16			150 SACKS
Cond. 13-10"	63	63	
9 5/8	170		
8 5/8	760		
7	1160		
5 1/2			
4 1/2		2425	
3			
2		2420	
Liners Used			

Well treatment details:  
20,000 LB SAND 500 GALL NAID  
TWO ZONES - BEREA + GORDON  
PRODUCED FROM BOTH SANDS

Attach copy of cementing record.

Coal was encountered at NONE Feet \_\_\_\_\_ Inches \_\_\_\_\_  
Fresh water 70 - 232 - 281 Feet \_\_\_\_\_ Salt Water \_\_\_\_\_ Feet \_\_\_\_\_  
Producing Sand BEREA + GORDON Depth 2299 - 2421

Formation	Color	Hard or Soft	Top Feet	Bottom Feet	Oil, Gas or Water	* Remarks
SURFACE	SAND & GRAVEL		50			
SAND			50	70		
SHALE			70	170		
ROCK			170	246		
SHALE			246	1100		
SAND (MEDIUM)			1100	1112		SHOW OIL
SAND + SHALE STREAKS			1112	1480		
SAND + LIME STREAKS			1480	1736		
BLACK HARD SHALE			1736	2230		
BEREA SAND			2230	2238		OIL + GAS
BLACK HARD SHALE			2238	2417		
GORDON SAND			2417	2425		OIL + GAS