

J. E. Sharp No. 13 Well

Sherman District, Calhoun County, W. Va.

By South Penn Natural Gas Company, Parkersburg, W. Va.

Located 4.54 mi. N. of 51°00' and 0.24 mi. S. of 35°30' - SE - Arnoldsbury Quadrangle.

Elevation 1015.69' L.

Permit Cal-714

Drilling commenced Aug. 29, 1942; completed Nov. 21, 1942.

Shot Dec. 8, 1942, depth 2216-2235' with 90 qt. bomb.

Oil well, 40 bbls. weekly after shot.

Section based on samples from 2150 to 2240' examined by J. H. C. Hartman.

Top Bottom Thickness

Greenbrier Limestone, 140 feet

2087			Top "Big Line" in driller's record
2150	2160	10	Limestone, light-brown, slightly sandy
2160	2170	10	Limestone, light-brown, very sandy
2170	2180	10	Limestone, very light-brown
2180	2190	10	Sandstone, light-brown, fine, calcareous
2190	2195	5	No sample
2195	2200	5	Limestone, light-brown and gray, with much rust stain
2195	2200	11	Limestone, light-brown, very sandy, with some oolites
2200	2235	17	Limestone, very light-brown, dolomitic, sandy; contains a few small green specks; sandy dolomite toward bottom of interval; slightly porous, 2212-2215' and much more so, 2218-2225' (oil pay 2218-2235')
2235	2245	9	Dolomite, very light brown, sandy, porous; larger sand grains are rounded and frosted

Penns Formation, 11+ feet

2235	2245	11 Shale, gray, with small specks of siderite
		Total depth