

KAN-600-D  
800-D?

Ray Salyers No. 2 Well

Poca District, Kanawha County, W. Va.

By South Penn Natural Gas Company, Parkersburg, W. Va.

Located 3.3 mi. W. of 81°30' and 1.7 mi. S. of 38°55' - SE - Kenna Quadrangle.

Elevation 646.16'.

Permit Kan-600 D

Completed to 1507' in 1941, with 3,499,000 cu. ft. gas in Big Lime. Deepened in April 1942 and treated with 1500 gallons acid in Big Lime.

Oil - 16 bbls. 1st 24 hrs.

Section based on samples from 1509 to 1567', examined by J.H.C. Hartens.

Top Bottom Thickness

Greenbrier Limestone, 119+ feet

| Top  | Bottom | Thickness | Description  |
|------|--------|-----------|--|
| 1443 |        |           | Top Big Lime in driller's record                               |
| 1509 | 1514   | 5         | Limestone, very light brown, oolitic and porous                |
| 1514 | 1519   | 5         | Limestone, very light brown                                    |
| 1519 | 1525   | 6         | Limestone, very light brown, oolitic and sandy                 |
| 1525 | 1552   | 27        | Limestone, very light brown and light-gray                     |
| 1552 | 1567   | 15        | Limestone, very light brown, oolitic, porous (gas and oil pay) |
|      | 1567   |           | Total depth  |